

## Fiberglass Stepladder CSA Grade 1 - RED



- Non-conductive Fiberglass Rails
- Double Riveting on each step
- Heavy-duty molded plastic top
- Back-up Plates Reinforce all Top Connections
- Extra Heavy-duty Inside Spreader Bars
- Extra Heavy-duty Full 3" Serrated Aluminum Steps
- Heavy-duty Slip Resistant Feet
- Rails: 1-1/4" x 3-1/16"
- Legs: 1-1/4" x 1-5/16"

**EXTRA HEAVY-DUTY INDUSTRIAL  
CSA GRADE 1, ANSI 1A  
300 LBS. DUTY RATING**

Part #	Size (FT.)	Weight (LBS.)
STUF486-03	3	14
STUF486-04	4	15
STUF486-05	5	18
STUF486-06	6	20
STUF486-08	8	26
STUF486-10	10	37
STUF486-12	12	46

## Fiberglass Stepladder CSA Grade 1 - YELLOW



- Non-conductive Fiberglass Rails
- Double Riveting on each step
- Heavy-duty molded plastic top
- Back-up Plates Reinforce all Top Connections
- Heavy-duty Outside Spreader Bars
- Heavy-duty Full 3" Serrated Aluminum Steps
- Heavy-duty Slip Resistant Feet
- Rails: 1-1/8" x 3-1/16"
- Legs: 1-1/8" x 1-1/2"

**HEAVY-DUTY  
CSA GRADE 1, ANSI 1  
250 LBS. DUTY RATING**

Part #	Size (ft.)	Weight (lbs.)
STUF540-04	4	11
STUF540-05	5	13
STUF540-06	6	16
STUF540-08	8	22

## Wood Stepladder - 89 Series w/Black End Caps



- Manufactured from clear Straight- Grain Lumber
- Rods under every step
- Cross bracing on back legs
- Plastic caps (Black) on top to prevent chipping
- Locking - type quick action spreader
- Side Rails: 1-1/16" x 2-3/4"
- Legs: 1-1/16" x 1-3/4"
- Steps: 7/8" x 3"
- Paint Tray

**HEAVY-DUTY INDUSTRIAL  
MEETS AND EXCEEDS, CSA GRADE 1  
250 LBS. DUTY RATING**

Part #	Size (ft.)	Weight (lbs.)	Part #	Size (ft.)	Weight (lbs.)
STU89-03	3	10	STU89-08	8	28
STU89-04	4	14	STU89-10	10	35
STU89-05	5	18	STU89-12	12	42
STU89-06	6	21	STU89-14	14	56
STU89-07	7	25			

## Wood Stepladder - 99 Series w/Yellow End Caps



- Manufactured from clear Straight- Grain Lumber
- Rods under every step
- Rungs brace back legs
- Plastic caps (Yellow) on top to prevent chipping
- Locking - type quick action spreader
- Side Rails: 1-5/16" x 2-5/8"
- Legs: 1-5/16" x 2-1/4"
- Steps: 7/8" x 3"

**EXTRA HEAVY-DUTY INDUSTRIAL  
MEETS & EXCEEDS, CSA GRADE 1 ANSI 1A,  
300 LBS. DUTY RATING**

Part #	Size (ft.)	Weight (lbs.)	Part #	Size (ft.)	Weight (lbs.)
STU99-03	3	14	STU99-10	10	45
STU99-04	4	18	STU99-12	12	54
STU99-05	5	23	STU99-14	14	63
STU99-06	6	27	STU99-16	16	72
STU99-07	7	32	STU99-18	18	81
STU99-08	8	36	STU99-20	20	90

## Aluminum Stepladder CSA Grade 1



- Unsurpassed structural strength
- Large aluminum top with tool tray
- Massive side plates with four rivets per side
- Extra heavy duty pail shelf
- Inside spreaders on 8' and larger
- Deeply serrated aluminum steps
- Extra heavy back bracing

**CSA GRADE I, ANSI TYPE IA  
300 LBS. RATED**

Part #	Size (FT.)	Weight (LBS.)
STUA412-04	4	17
STUA412-05	5	21
STUA412-06	6	24
STUA412-08	8	33
STUA412-10	10	42
STUA412-12	12	52
STUA412-14	14	61
STUA412-16	16	69

## Aluminum Stepladder CSA Grade 1



- Ideal for heavy industrial and contractor use.
- Full U-channel front legs and double solid rivet construction.
- Full U-channel back legs with U-channel horizontal back bars, each fully braced.
- Sizes 3' to 12'.

**CSA GRADE I, ANSI TYPE I  
250 LBS. RATED**

Part #	Size (ft.)	Weight (lbs.)
STUA403-03	3	9
STUA403-04	4	12
STUA403-05	5	14
STUA403-06	6	17
STUA403-08	8	25
STUA403-10	10	31
STUA403-12	12	37

## Aluminum Sawhorse "MUSTANG"



- Heavy-duty aluminum extrusion
- Double Solid rivet construction
- Non-slip feet
- Heavy-duty spreaders for long trouble-free use
- Folding compact design for easy transportation
- Packed on skids for easy warehouse handling.

"IT'S A SAWHORSE AND A WHOLE LOT MORE"  
300 lbs. Rated

Part #	Size (FT.)	Top (in.)	Base (in.)	Spread (in.)	Weight (LBS.)
STU130-02	2	30	42"	68	40
STU130-25	2-1/2	30	34	25	13
STU130-03	3	30	35	29	15
STU130-04	4	30	36	36	20
STU130-05	5	30	37	44	25
STU130-06	6	30	38	51	30
STU130-08	8	30	38	51	30

## Heavy Duty Fiberglass Extension Ladder



- Non-conductive fiberglass rails
- Heavy duty self-aligning safety feet with ice-pick plate
- 1-5/8" safety serrated D-ring
- Polyethylene rung sleeves to reduce wear
- Extra heavy-duty spring assisted gravity locks

CSA CERTIFIED GRADE 1  
ANSI TYPE 1A  
300 LBS. DUTY RATING

Part #	Size (FT.)	Ext. (FT.)	In Fly (in.)	Out Fly (in.)	Weight (LBS.)
STUF534-16	16	13	13-3/4	17-1/2	35
STUF534-20	20	17	13-3/4	17-1/2	42
STUF534-24	24	21	13-3/4	17-1/2	50
STUF534-28	28	25	13-3/4	17-1/2	57
STUF534-32	32	29	14-15/16	17-11/16	68
STUF534-36	36	32	14-15/16	17-11/16	77
STUF534-40	40	35	14-15/16	17-11/16	86

## Aluminum Extension Ladder



- EXTRA LARGE D-RUNG.
- Yellow protective end caps.
- Full I-Beam side rails
- Spring loaded die cast zinc locks.
- Rugged extruded safety shoes with ice pick feet.
- C.S.A. Certified.

CSA GRADE 1

Part #	Size (FT.)	Ext. (FT.)	Width (FT.)	Weight (LBS.)
STU7716	16	13	17 1/2	25
STU7720	20	17	17 1/2	30
STU7724	24	21	17 1/2	35
STU7728	28	25	17 1/2	50
STU7732	32	29	17 1/2	57
STU7736	36	32	17 1/2	71
STU7740	40	36	17 1/2	78

## Aluminum Sawhorse Flat-Top



- Heavy-duty aluminum extrusion
- Double Solid rivet construction
- Non-slip feet
- Heavy-duty spreaders for long trouble-free use
- Folding compact design for easy transportation

10" WIDE TOP-STEP  
300 lbs. Rated

Part #	Size (FT.)	Top (in.)	Base (in.)	Weight (LBS.)
STU140-02	2	30	33	12
STU140-25	2-1/2	30	34	15
STU140-03	3	30	35	17
STU140-04	4	30	36	23

## Aluminum Box Rail Extension Ladder



- ROUND RUNG
- YELLOW protective end caps.
- Full RECTANGULAR BOX Beam side rails
- Spring loaded die cast zinc locks.
- Rugged STEEL safety shoes with ice pick feet
- Side-mounted pulley and rope
- Sleeves on base section rungs to stop chaffing

CSA GRADE 1, ANSI TYPE 1A  
300 LBS. RATED.

Part #	Size (FT.)	Ext. (FT.)	Width (FT.)	Weight (LBS.)
STUA132-16	16	13	17 1/4	30
STUA132-20	20	17	17 1/4	33
STUA132-24	24	21	17 1/4	42
STUA132-28	28	25	17 1/4"	47
STUA132-32	32	29	17 1/4	53
STU4236	36	32	18 1/2"	71
STU4240	40	36	18 1/2	80

## Aluminum Extension Ladder



- Interlocking channel side rails 3" deep x 1" wide
- D-rung
- Die-cast ladder locks with stainless steel springs.
- Safety feet with ice pick
- C.S.A. Certified.

CSA GRADE 2

Part #	Size (FT.)	Ext. (FT.)	Width (FT.)	Weight (LBS.)
STU5716	16	13	17 1/4	24
STU5720	20	17	17 1/4	30
STU5724	24	21	17 1/4	35
STU5728	28	25	17 1/4	45
STU5732	32	28	17 1/4	52
STU5736	36	32	17 1/4	61
STU5740	40	36	17 1/4	69

## 504 Series - HD Industrial Wood Stepladder



Type 1A  
300 lbs.

**ALLRIGHT**

- High-quality clear straight-grain lumber with eased edges
- Front steps flush with siderails
- Tie rods under every step
- Heavy-duty plywood top
- End caps on top to prevent chipping
- Wrap-around head irons;
- Inside pinch resistant one piece spreader
- c/w paint tray.
- Front Rails: 1-1/16" x 2-3/4"
- Back Rails: 1-1/16" x 1-3/4"
- Steps: 7/8" x 3-1/4"

Part #	Size (FT.)	Width (in.)	Spread (in.)	Weight (LBS.)
ALL504-03	3	18	23	10
ALL504-04	4	20	30	14
ALL504-05	5	21	35	18
ALL504-06	6	23	42	21
ALL504-07	7	24	46	25
ALL504-08	8	26	51	28
ALL504-10	10	29	62	35
ALL504-12	12	33	74	42
ALL504-14	14	36	87	56

## S Series - Frame Scaffold



**ALLRIGHT**

- Flexible and expandable to meet a wide variety of requirements in construction and maintenance
- Access both high and wide areas with multiple persons

Part #	Description	Weight (LBS.)
ALLSMF6060P	Mason Frame 60"H x 60"W	43
ALLSBR0704	Crossbrace 7' x 4'	10
ALLSBR1004	Crossbrace 10' x 4'	14
ALLSGR0700	Guardrail 7'	4
ALLSGR1000	Guardrail 10'	6
ALLSSJ24	24" Screwjack - Solid Post	12
ALLSCS08	8" Caster	12
ALLSAD0719	Alum/Ply Deck 19"W x 7'	32
ALLSAD1019	Alum/Ply Deck 19" W x 10'	46

## 560 Series - Aluminum Trestle / Walk-Up Scaffold



Type 1A  
300 lbs.

**ALLRIGHT**

- For use as a double front ladder, sawhorse or workbench
- Steps on both sides for dual access and dual use
- Heavy-duty aluminum extrusion
- Solid rivet construction
- Heavy-duty spreader
- Durable PVC molded non-slip feet
- Folding compact design for easy storage and transport
- Ideal for use with extension or aluminum planks

Part #	Size (FT.)	Width (in.)	Spread (in.)	Weight (LBS.)
ALL560-02	2	33	21	11
ALL560-25	2-1/2	34	25	14
ALL560-03	3	35	29	16
ALL560-04	4	36	36	21
ALL560-05	5	37	44	26
ALL560-06	6	38	51	31
ALL560-08	8	40	65	41

## S600 Series - Rolling Tower Scaffold



1000 lbs.

**ALLRIGHT**

- Quick assembly and adjustment
- Fits through doorways 30" and wider
- End frames offset for secure use on stairways
- Locking truss pins
- Trussed plywood deck
- Grooved rungs on end frame for added safety
- 5" two-way pinned locking casters
- 3 unit maximum height: 18-1/2" with outriggers

Part #	Size (FT.)	Width (in.)	Spread (in.)	Weight (LBS.)
ALLS600-00	6	29	72	132
Unit consists of: 2 - End frames; 2 - Trusses; 1 - Plywood deck, 4 - Locking casters				
<b>ACCESSORIES</b>				
ALLS600-02	Guardrail Kit (each)			44
ALLS600-03	Outriggers (each)			7

**ALLRIGHT**

PRODUCTS ARE ONLY AVAILABLE  
IN BRITISH COLUMBIA



600 Series Rollina Tower Scaffold



- Stackable to 18.5' (3 sections), with outriggers and guardrails.
- 1000 lbs. rated
- Yellow

**SCAFFOLD KIT: 1 DECK, 2 TRUSSES, 2 END FRAMES, 4 CASTERS**

Part #	Description
STU600S	Scaffold kit: 1 deck, 2 trusses, 2 end FRAMES, 4 casters
STU600S-02	Guardrail kit
STU600S-03	Outrigger Kit (4 pcs.)
STU600S-05	5" Caster (1)
STU600S-HS	3' Half- section (no casters included)
STU600S-07	Plywood deck (1)
STU600S-08	Truss (1)
STU600S-11	End frame (1)

Scaffold Deck



Part #	Description	Size
STUAP0719	Aluminum/Plywood Deck	7' x 19"
STUAP1019	Aluminum/Plywood Deck	10' x 19"

All Aluminum Plank



- Engineered for strength yet very light
- Safety grate aluminum surface is especially effective in slippery or muddy conditions
- Aluminum surface will not de-laminate like plywood resulting in extended plank life
- All-aluminum construction suitable for outdoor storage
- For use with ladder jacks, pump jacks or aluminum sawhorses
- Complete with connector kit installed both ends.

**TWO-MAN  
500 lbs. DUTY RATING**

Part #	Length (ft.)	Width (in.)	Weight (lbs.)
STUA1212	12	12	40
STUA1216	16	12	52
STUA1220	20	12	68
STUA1224	24	12	79
STUA1812	12	18	53
STUA1816	16	18	72
STUA1820	20	18	92
STUA1824	24	18	115

505 Series Frame Scaffold



- Frame includes - 2 connectors

**POWDER COATED**

Part #	Description
STU505-01	5' x 5' Frame

505 Series Scaffold Brace



**GALVANIZED BRACE**

Part #	Description
STU505-02	10' x 4"
STU505-06	7' x 4"



## Ladder Jacks



- Double sided-slotted level adjustment for strength and stability.
- 250 lbs rated per jack.
- Level adjustment allows the jack to be mounted on inside or outside of ladder.
- Top hook / bottom leaning anchoring system. (Preferred style by end-user)
- Fits all D-rung extension ladders

Part #	Description	Qty.
STU670	Ladder Jacks	1 Pair

## The Transformer - Telescoping Ladder System



- Stores at a height of 6', 5' and 4'
- 300 lbs. duty rating
- Can be a step ladder/double front ladder, single ladder, stair/off-set ladder
- Included are hinges for scaffold configuration
- Detailed users hand book
- Protective head and exterior P.O.S. clear packaging

Part #	Step Ladder (ft.)	Ext. Ladder (ft.)	Weight (lbs.)
STULGL-04	4-7	7-11	41
STULGL-05	5-9	10-18	54
STULGL-06	6-11	12-22	65

## 505 Series Scaffold Screw Jack



SOLID STEEL SCREW JACK

Part #	Description
STU505-03	Solid Steel Screw Jack

## 505 Series Scaffold Pig Tail



Part #	Description
STU505-04	Steel - ITEM NOT SHOWN

## 505 Series Scaffold Caster



Part #	Description
STU505-05	8" Caster with 2-way locking

