



ADHESIVES & CAULKING

SCS1700 SANITARY



Mildew-resistant sealant for ceramic tile, showers, tubs and plumbing fixtures.

Joint Movement Capability (ASTM C719)	+/- 25%
Ultimate Elongation	373%
Ultimate Tensile Strength	292 psi (2.0 MPa)
VOC	20 g/L
Work Life (tooling time)	5-10 minutes

Part #

LPG1134886
LPG1116110

SCS2000 SilPruf*



A high-strength weatherproofing silicone sealant and structural glazing adhesive.

Joint Movement Capability (ASTM C719)	+/- 50%
Tear Strength (die B)	76.8 ppi
Ultimate Elongation	715%
Ultimate Tensile Strength	341 psi (2.35 MPa)
VOC	20 g/L
Work Life (tooling time)	20-30 minutes
Fire Endurance (UL723, ASTM E814)	2 hours (with backer)
Hardness, Durometer (type A)	24

Part #

LPG1134884
LPG1116109

SCS1200 CONSTRUCTION



Premium glazing sealant for structural as well as general purpose glazing.

Joint Movement Capability (ASTM C719)	+/- 25%
Ultimate Elongation	513%
Ultimate Tensile Strength	480 psi (3.31 MPa)
VOC	23 g/L
Work Life (tooling time)	5-10 minutes

Part #

LPG1104776

SCS1800 CONTRACTORS-N



For general purpose glazing and sealing applications, neutral cure.

Joint Movement Capability (ASTM C719)	+/- 50%
Ultimate Elongation	520%
Ultimate Tensile Strength	200 psi (1.38 MPa)
VOC	32 g/L
Work Life (tooling time)	6-12 minutes

Part #

LPG1105695

SWS



A neutral-cure silicone sealant for basic joint sealing applications.

Joint Movement Capability (ASTM C719)	+/- 35%
VOC	20 g/L
Work Life (tooling time)	30-40 minutes
Hardness, Durometer (type A)	22

Available in 10 standard colors designed to match many typical commercial window frames.

Part #

LPG10-02002-0

SCS1000 CONTRACTORS



For general purpose glazing and sealing applications.

Joint Movement Capability (ASTM C719)	+/- 25%
VOC	20 g/L
Work Life (tooling time)	5-10 minutes

Part #

LPG648237
LPG628822

3M™ Scotch-Weld™ Nitrile High Performance Plastic Adhesive 1099



3M™ Scotch-Weld™ Nitrile High Performance Plastic Adhesive 1099 is a fast drying and heat curable plastic adhesive.

Catalog ID	Size
3MA1099	1QT
3MA1099L	5GAL

3M™ Scotch-Weld™ Neoprene High Performance Contact Adhesive 1357



3M™ Scotch-Weld™ Neoprene High Performance Contact Adhesive 1357 Gray-Green is a high-performance contact adhesive.

Catalog ID	Size
3MA1357	1QT

3M™ Scotch-Weld™ Neoprene High Performance Rubber And Gasket Adhesive 1300



3M™ Scotch-Weld™ Neoprene High Performance Rubber And Gasket Adhesive 1300 is a yellow solvent type synthetic rubber based adhesive.



Catalog ID	Size
3MA1300	5OZ
3MA1300	1QT

3M™ Ten Bond



A brushable, neutral-colored contact adhesive for bonding many decorative laminates, aluminum, steel, plywood, panels, wood and wood veneer, masonry, rubber, canvas and other porous and non-porous materials to each other or to themselves where traditionally using solvent to bond laminate quickly.



Catalog ID	Size	Description
3MA10BOND	1LTR	
3MA10BOND	1GAL	
3MA10BOND	5GAL	
3MAACT1L	1LTR	Activator

3M™ Fastbond™ Contact Adhesive 2000NF



3M™ Fastbond™ Contact Adhesive 2000NF is a water-dispersed, high solids, activated adhesive.



Catalog ID	Size
3MA2000NF	5GAL/50GAL

3M™ Fastbond™ Contact Adhesive 30NF



3M™ Fastbond™ Contact Adhesive 30NF is a water-dispersed high strength contact adhesive. Water Dispersed, Sprayable Contact Adhesive with High Immediate Bond Strength and a Long Bonding Range that Changes Color from Blue to Green (green) or White to Clear (neutral) When it is Dry.



Catalog ID	Size	
3MA30CA	1L	GREEN
3MA30CA	1GAL	GREEN
3MA30CA	1GAL	NEUTRAL
3MA30CA	5GAL	NEUTRAL
3MA30CA	52GAL	NEUTRAL



ADHESIVES & CAULKING

3M™ Scotch-weld™ Industrial Plastic Adhesive 4475



3M™ Scotch-weld™ Industrial Plastic Adhesive 4475 is a clear, fast drying adhesive with resistance to plasticizers, water, detergents and soap solutions.

Catalog ID	Size
3MA4475	5OZ

3M™ Scotch-Weld™ High Performance Industrial Plastic Adhesive 4693



3M™ Scotch-Weld™ High Performance Industrial Plastic Adhesive 4693 is a solvent-based, synthetic rubber adhesive

Catalog ID	Size
3MA4693	1GAL

3M™ Scotch-Weld™ High Performance Industrial Plastic Adhesive 4693



3M™ Scotch-Weld™ High Performance Industrial Plastic Adhesive 4693 is a solvent-based, synthetic rubber adhesive

Catalog ID	Size
3MA4693	1GAL

3M™ Fastbond™ Insulation Adhesive 49



3M™ Fastbond™ Insulation Adhesive 49 is a water-based, high solids, fast tacking, pressure sensitive adhesive. Low voc and Leed compliant.



Catalog ID	Size
3MA49	5GAL

3M™ Pressure Sensitive Spray Adhesive 72



3M™ Pressure Sensitive Spray Adhesive 72 is a permanently tacky industrial grade spray adhesive. Aggressive adhesive, long open time and repositionable. Adheres to plastic, foam padding, carpet backing, polyethylene and polypropylene.

Catalog ID	Size
3MA72	24OZ

3M™ FoamFast Spray Adhesive 74



For Bonding Flexible Urethane or Latex Foam Together or to Many Other Materials Like Wood, Metal, and Non-Vinyl Plastics.

Catalog ID	Size
3MA74	24OZ



ADHESIVES & CAULKING

3M™ Hi-Tack Spray Adhesive 76



Quick-Tacking, Fast Strength Buildup. Aerosol, for Bonding Hard to Hold Materials Like Polyethylene and Polypropylene. SBR Rubber, Fabric and Felt.

Catalog ID	Size
3MA76	24OZ

3M™ Super 77 Spray Adhesive



High tack, high coverage and fast drying for permanently attaching foils, carpeting, lightweight paper, cardboard, felt and, cloth to painted or unpainted metals, wood, hardboard and other base materials.

Catalog ID	Size
3MA77	24OZ

3M™ Rubber And Vinyl 80 Spray Adhesive



3M™ Rubber And Vinyl 80 Adhesive Spray Adhesive is a high performance neoprene based contact aerosol spray adhesive. Resists plasticizer which causes regular adhesives to "let go."

Catalog ID	Size
3MA80	24OZ

3M™ Hi-Strength 90 Spray Adhesive



High strength, fast contact-type adhesive. Fast contact strength buildup for many decorative laminates. Only needs one minute of drying time.

Catalog ID	Size
3MA90	24OZ
3MA90	5GAL

3M™ Super Trim Adhesive



Super Trim Adhesive -Aerosol contact adhesive designed for bonding vinyl tops, heavyweight liners and hood silencer pads where high strength and heat resistance are needed.

Catalog ID	Size
3MA08090	19OZ

3M™ Scotch-Weld™ Hi-Strength Postforming 94 CA Cylinder Spray Adhesive



3M™ Scotch-Weld™ Hi-Strength Postforming 94 CA Cylinder Spray Adhesive is a low VOC, high performance, postformable grade spray adhesive with a unique low telegraphing pebble spray pattern.

Catalog ID	Size
3MA94CA-CLR	5GAL /26.2LB /128LB



3M™ Fastbond™ Foam Adhesive 100NF



3M™ Fastbond™ Foam Adhesive 100NF is a water dispersed neoprene contact adhesive.



Catalog ID **Size**
3MAFBNDL100 5GAL

3M™ Polyurethane Sealant 540



3M™ Polyurethane Sealant 540 is a one component, moisture curing products which form permanently elastic bonds.

Catalog ID **Colour**
3MA540CART WHITE/GREY/BLACK

3M™ Polyurethane Adhesive Sealant 560



3M™ Polyurethane Adhesive Sealant 560 is a very strong one component, moisture curing products which form permanent elastic bonds.

Catalog ID **Colour**
3MA560CART WHITE/GREY/BLACK

3M™ Hybrid Adhesive Sealant 760



3M™ Hybrid Adhesive Sealant 760 is a single component, high strength, elastomeric sealant. This hybrid technology is paintable when wet and will not degrade when exposed to UV.

Catalog ID **Colour**
3MA760 WHITE /BLACK/GREY

3M™ Hybrid Adhesive Sealant 730



3M™ Hybrid Adhesive Sealant 730 is a single component, high strength, elastomeric sealant. This hybrid technology is paintable when wet and will not degrade when exposed to UV.

Catalog ID **Size**
3MA730 WHITE /BLACK/GREY

3M™ Scotch-Weld™ Instant Adhesive Surface Activator



3M™ Scotch-Weld™ Instant Adhesive Surface Activator is a surface activator for instant adhesives.

Catalog ID **Size**
3MACA 2OZ

3M™ Scotch-Weld™ Instant Adhesive CA40



3M™ Scotch-Weld™ Instant Adhesive CA40 is a low viscosity, very fast-setting instant adhesive for rubbers and elastomers.

Catalog ID	Size
3MACA-40	1OZ

3M™ Scotch-Weld™ Epoxy Adhesive DP110



3M™ Scotch-Weld™ Epoxy Adhesive DP110 is a flexible, two-part epoxy. 1:1 mix ratio, 10 minute work life and handling strength in 20 minutes. 3M™ Scotch-Weld™ EPX™ Plus II.

Catalog ID	Size
3MADP-110	1.7OZC

3M™ Scotch-Weld™ Epoxy Adhesive DP420



3M™ Scotch-Weld™ Epoxy Adhesive is a toughened, two-part epoxy. 2:1 mix ratio. Great impact resistance.

Catalog ID	Size	Description
3MADP-420	1.25OZ	Fast Cure
3MADP-460	1.25OZ	Slow Cure

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS



3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS is a clear, non-sag, toughened, two-part acrylic adhesive. 1:1 mix ratio, 10 minute work life and handling strength in 20 minutes. Metal to metal bonding.

Catalog ID	Size
3MADP810	1.7OZ

3M™ Scotch-Weld™ EPX™ Plus II Applicator



3M™ Scotch-Weld™ EPX™ Plus II Applicator for use with 1:1 50mL, 2:1 37mL and 3:2 43mL cartridges. A separate plunger can be ordered for the 10:1 37mL cartridge.

Catalog ID
3MAEPXPLUSII

3M™ Scotch-Weld™ EPX™ Mixing Nozzle



3M™ Scotch-Weld™ EPX™ Mixing Nozzle for use with 10:1 35mL cartridges.

Catalog ID
3MAEPXPLUSNOZ54



ADHESIVES & CAULKING

3M™ Scotch-Weld™ EPX™ Plus II Mixing Square Nozzle Gold




3M™ Scotch-Weld™ EPX™ Plus II Mixing Square Nozzle Gold fits 1:1 50mL, 2:1 37mL and 3:2 43mL cartridges.

Catalog ID

3MAEPX-SQNOZZLE

3M™ Scotch-Weld™ Hot Melt Adhesive 3762 TC, 3764 TC, 3792 LM Q



3M™ Scotch-Weld™ Hot Melt Adhesive 3762 TC is a 100% solids thermoplastic adhesive. Excellent "Hot Tack". Designed for packaging applications. 3M™ Scotch-Weld™ Hot Melt Adhesive 3764 TC is a clear, 100% solids thermoplastic adhesive. 3M™ Scotch-Weld™ Hot Melt Adhesive 3792 LM Q is a low-melt with long bonding range adhesive. Quadrack version. 3M™ Scotch-Weld™ Hot Melt Adhesive 3762 LM Q is a low melt, 100% solids thermoplastic adhesive. Excellent "Hot Tack". Designed for packaging applications.

Catalog ID

3MA3762Q

3MA3762LMTCQ

3MA3764Q

3MA3792LMTCQ

3M™ Scotch-Weld™ Hot Melt Applicator TC



3M™ Scotch-Weld™ Hot Melt Applicator TC with Quadrack Converter and Palm Trigger.

Catalog ID

3MALT-QUADRACK

Description

For Low Melt Adhesive

3M™ High Power Aerosol Brake Cleaner



A high power aerosol brake cleaner. Cleans brake dust, grease, oil and other contaminants. Contains 45% VOC - Not for sale in California.

Catalog ID

3MA08180

Size

14oz

3M™ Rust Fighter



Rust Fighter Internal panel coating used for corrosion protection. Ideal for restoring corrosion protection following the repair of hem flanges, door skins, rocker panels, and similar areas.

Catalog ID

3MA08892

Size

530gm

3M™ Adhesive Cleaner



Adhesive Cleaner specially blended solvent for removal of light paint overspray, adhesive residue, wax, grease, tree sap, dirt, road tar, oil and bugs in aerosol form. Will not harm most thoroughly cured automotive paint, vinyls, or fabrics when properly used.

Catalog ID

3MA08987

Size

425gm



ADHESIVES & CAULKING

PL Premium® - 100% Polyurethane Adhesive



Provides superior results and is safer to use. Great for a variety of materials.

PL Premium® is a polyurethane adhesive that provides superior results and is safer to use. PL Premium® generates three times the power of traditional construction adhesives. It may be used inside or outside and will last as long as the surfaces it joins together.

Part #	Colour Family	Size	Case Pack
LPGPL393971	Bronze	310mL	20
LPGPL393970	Bronze	825mL	12

PL200® - Construction Adhesive



Great for paneling and drywall

PL200® is a premium grade adhesive for paneling, drywall and other light construction, inside or outside.

Part #	Colour Family	Size	Case Pack
LPGPL1113127	Tan	300mL	12
LPGPL1113121	Tan	825mL	12

PL300® - Foamboard Adhesive



Great for applying foamboard insulation to substrate

PL300® provides dependable adhesion of foam to all types of surfaces, including wood, fiberglass panels, concrete, brick, metal and drywall. It is compatible with foam board insulation. It permanently joins the foam to the substrate without compromising the value of the foam.

Part #	Colour Family	Size	Case Pack
LPGPL1113124	Tan	300mL	12
LPGPL1113123	Tan	825mL	12

PL400® - Sub-Floor & Deck Adhesive



Used for heavy duty construction when a powerful bond is required



PL400® provides the ultimate in bonding capabilities and is specially formulated for all heavy duty construction, interior or exterior . . . wherever a powerful, permanent bond is required.

Part #	Colour Family	Size	Case Pack
LPGPL790543	Tan	300mL	12
LPGPL526370	Tan	825mL	12

PL® 9000 - Heavy Duty Construction Adhesive



Provides extremely high initial grab and rapid bond strength



PL® 9000 provides extremely high initial grab and rapid bond strength development while bridging gaps. Cures to yield exceptionally strong, permanent and weather resistant bonds.

Part #	Colour Family	Size	Case Pack
LPGPL790546	Tan	300mL	12

PL Polyurethane® - Concrete Crack & Masonry Sealant - Window, Door & Siding Sealant - Roofing & Flashing Sealant



PL Polyurethane® Concrete Crack & Masonry Sealant
PL Polyurethane® Window, Door & Siding Sealant
PL Polyurethane® Roofing & Flashing Sealant

These are premium quality, commercial grade sealants-developed specially for forming permanent, water and weatherproof seals in most exterior gaps and joints. This sealant is elastic which accommodates construction material movement to protect the original seal.

Part #	Colour Family	Size	Case Pack
LPGPL394143	Limestone	300mL	12
LPGPL394144	White	300mL	12
LPGPL394149	Black	300mL	12

GREEN SERIES™ - Multi-Purpose Drywall & Panel

NEW

Henkel



Designed for drywall applications and fabricating shear wall assemblies



Green Series™ Multi-Purpose Drywall & Panel is a high performance latex-based construction adhesive designed for drywall applications and fabricating shear wall assemblies. This adhesive is non-flammable, environmentally friendly and VOC compliant for all interior & in-plant construction use. Product offers fast strength development with high shear strength values.

Part #	Colour Family	Size	Case Pack
LPG1134886	White	300mL	12
LPG1116110	White	825mL	12

GREEN SERIES™ - Sub-Floor & Deck

NEW

Henkel



Developed for Glued Floor System



Green Series™ Sub-Floor & Deck Adhesive is a professional grade, non-flammable, environmentally friendly construction adhesive developed for Glued Floor Systems and other interior or exterior general construction. The product's unique formulation offers fast strength development and excellent gap filling characteristics. Provides a strong yet flexible permanent bond to most building materials. NOTE: Not recommended for composite decking.

Part #	Colour Family	Size	Case Pack
LPG1134884	White	300mL	12
LPG1116109	White	825mL	12

GREEN SERIES™ - Draft & Acoustical

NEW

Henkel



Designed for the reduction of sound transmission and drafts in all types of wall systems



Green Series™ Draft & Acoustical Sealant is a non-flammable, latex based sealant specifically designed for the reduction of sound transmission and drafts in all types of wall systems. Remains flexible and adheres firmly to wood, metal studs, concrete, gypsum board and most other building materials. Soap & water clean up.

Part #	Colour Family	Size	Case Pack
LPG1104776	White	825mL	12

GREEN SERIES™ - All-Purpose Sealant

NEW

Henkel



Designed for sealing gaps and cracks around doors and windows



Green Series™ All-Purpose Sealant is a high performance sealant designed for sealing gaps and cracks around doors and windows, indoor and out. This water based, low VOC formula makes it ideal for use indoors with the durability, flexibility and adhesive strength needed for outdoor use. Dries to a high gloss sheen that is paintable.

Part #	Colour Family	Size	Case Pack
LPG1105695	White	300mL	12

NO MORE NAILS® Ultra

NEW

Henkel



Ideal for bonding of wood decking to joists, fencing and siding (Aluminum and PVC)



No More Nails® Ultra is a high strength, premium quality, heavy duty adhesive which eliminates the need for nails and screws in many indoor or outdoor applications. No More Nails® Ultra is weather resistant, paintable and only requires water clean-up. Recommended for use on sub-floors, decks, wood, pressure-treated lumber, brick, concrete, aluminum, foam, cork, ceramic, tile. Ideal for bonding of wood decking to joists, fencing and siding (Aluminum and PVC). Water and mildew resistant. Dries white. Meets or exceeds AFG-01, ASTM D3498 and ASTM C557 specifications.

Part #	Colour Family	Size	Case Pack
LPG10-02002-0	White	300mL	12

PL® Acousti-Seal Vapour Barrier Sealant

Henkel



Provides an efficient seal to aid in the reduction of airborne sound transmission

PL® Acousti-Seal is specially formulated to adhere most common vapour barrier films to wood, metal, concrete, gypsum board, plaster and foam board. It also provides an efficient seal to aid in the reduction of airborne sound transmission in wall assembly systems.

Part #	Colour Family	Size	Case Pack
LPG648237	Black	300mL	24
LPG628822	Black	825mL	12



ADHESIVES & CAULKING

Pres-Tite® - Blue Contact Cement

Henkel



Ideal for laminating a wide variety of materials

Pres-tite® Blue is ideal for laminating rubber, metal, wood veneers, plywood, plastic laminates, cork, leather, fabric, paper products or a combination of these. Resistant to heat, creep, water and oil. Dries quickly and bonds immediately. Clamping is not required.

Part #	Colour Family	Size	Case Pack
LPG530532	Yellow/Tan	250 mL w/brush	12
LPG530531	Yellow/Tan	500 mL	12
LPG530530	Yellow/Tan	946 mL	6
LPG531216	Yellow/Tan	3.8 L	2

Pres-Tite® - Gel Contact Cement

Henkel



This no-drip formula is great for applying to vertical surfaces

Pres-tite® Gel is a unique, no-drip contact cement that allows for clean and easy applications to vertical surfaces. Pres-tite® Gel spreads smoothly without stringing. Laminates metal, wood veneers, plywood, plastic laminates, cork, leather, rubber, fabric, paper products or a combination of these. Dries quickly and bonds immediately. Clamping is not required.

Part #	Colour Family	Size	Case Pack
LPG647968	Yellow/Tan	946 mL	6

LePage® - Contact Cement Cleaner & Thinner

Henkel

For cleaner brushes and access cement from your substrate

Part #	Colour Family	Size	Case Pack
LPG537973	-	250 mL	12

Sumo™ Glue - Polyurethane Waterproof

Henkel



Sumo™ Glue is a revolutionary high strength polyurethane adhesive that is highly water and weatherproof, fast setting, gap filling and bonds a wide variety of materials and surfaces in both indoor and outdoor applications. Bonds wood, stone, foam, concrete, marble, metal, ceramics, leather, laminate and most other materials.

Part #	Colour Family	Size	Case Pack
LPG1114936	Yellow	100 mL	62

LePage Wood Glues - White Glue

Henkel



Ideal for the DIYer's

The DIYer's choice for general woodworking projects as well as for bonding paper, cardboard, leather and many other porous materials. Dries translucent and is non-toxic. Paintable and sandable. Perfect for the toolbox, garage and cottage. Ideal for use at home, workshop, office, craft room and classroom.

Part #	Colour Family	Size	Case Pack
LPG442183	White	400 mL	12
LPG524381	White	800 mL	6
LPG531252	White	3 L	3

LePage Wood Glues - Carpenter's Glue

Henkel



The best adhesive for woodworking projects

The Carpenter's and Cabinet Maker's choice whenever a fine woodworking project demands the best adhesive. Provides stronger initial tack, which helps keep work in alignment. And it sets faster - in just 15 to 25 minutes, which reduces clamping and assembly time. Dries translucent with superior sandability - so it won't clog up your sandpaper, and is also paintable. Bonds with two tons of strength.

Part #	Colour Family	Size	Case Pack
LPG442184	Yellow	400 mL	12
LPG649429	Yellow	800 mL	6
LPG530538	Yellow	3 L	3

LePage Wood Glues - Outdoor

Henkel



For all outdoor wood projects, when nails and screws just won't do

The Contractor's choice for all outside wood projects (deck, furniture, birdhouses, etc.); anytime weather is a factor and nails, screws or other fasteners just won't do. Exceeds ANSI/HPMA HP TYPE II water resistance testing. This is essential for an outdoor wood glue. Dries translucent. Paintable and sandable. All season durability; ideal for use when extreme climate conditions could affect the performance and longevity of a bond.

Part #	Colour Family	Size	Case Pack
LPG442185	Tan	400 mL	12

Instant Poly Filla®

Henkel



Ideal for small holes and cracks in plaster, wood, brick or concrete

Instant Poly Filla® is ideal for small holes and cracks in plaster, wood, brick or concrete. Instant Poly Filla® dries quickly for fast repairs. It takes nails and screws without breaking away. NOTE: Not for hanging pictures. For interior use only.

Part #	Colour Family	Size	Case Pack
LPG394026	White	162mL	12

Concrete Care - Poly Super Strength Cement®

Henkel



Used for repairing concrete, inside or out

Poly Super Strength Cement® repairs interior or exterior concrete, stone or brick. A polymer-modified mixture of high quality cement for improved adhesion especially to existing concrete. When cured it gives a smooth non-dusting surface, which resists water penetration and damage due to freezing. Can be coloured with dry earth pigments.

Part #	Colour Family	Size	Case Pack
LPG394026	White	162mL	12

Wood Filler - Plastic Wood®

Henkel



Can be sanded, sawed, varnished and painted

A high quality solvent-based wood filler which matches the working characteristics of wood. Contains wood fibres for fine texture and natural wood colour. Can easily be applied, sanded, sawed, painted and varnished. Excellent water resistance. Fast drying; low shrinkage and cracking.

Part #	Colour Family	Size	Case Pack
LPG1105356	Light Tan	117 mL	12
LPG1105356	Light Tan	235 mL	12
LPG1105356	Light Tan	473 mL	12
LPG1105356	Light Tan	946 mL	6

Tinted Wood Filler

Henkel



Professional quality tinted wood fillers

A high quality latex based indoor wood filler for fixing cracks, holes and surface imperfections. Cabinet maker's quality. Sandable, paintable. Different colours can be mixed and matched to obtain more accurate shades. Non-flammable, solvent free. Low odour.

Part #	Colour Family	Size	Case Pack
LPG442193	White	90 mL	12
LPG442194	Red Oak	90 mL	12
LPG393934	Natural	90 mL	12
LPG393935	Light Oak	90 mL	12
LPG393936	Teak	90 mL	12
LPG393937	Walnut	90 mL	12
LPG393938	Mahogany	90 mL	12

5 Minute Epoxy - 2 Part Syringe

Henkel



Bonds a wide variety of materials quickly & permanently

Speed Set™ Epoxy is available in several formats: dual syringe, professional size squeeze bottle and a precision instant mix applicator. Bonds metal, glass, ceramic, wood, masonry and many rigid plastics quickly and permanently. Sets in 5 to 8 minutes at room temperature. Dries transparent • Super strong • Water resistant

Part #	Colour Family	Size	Case Pack
LPG1165245	Amber	25 mL syringe	10

Speedy Set™ Epoxy

Henkel



Bonds a wide variety of materials quickly & permanently

Speed Set™ Epoxy is available in several formats: dual syringe, professional size squeeze bottle and a precision instant mix applicator. Bonds metal, glass, ceramic, wood, masonry and many rigid plastics quickly and permanently. Sets in 5 to 8 minutes at room temperature. Dries transparent • Super strong • Water resistant

Part #	Colour Family	Size	Case Pack
LPG1114597	Amber	2 x 118 mL bottles	6

Loctite Threadlockers

Henkel



By filling the thread roots and preventing side-to-side movement, Loctite threadlockers have dramatically increased the reliability of threaded assemblies for over 50 years.

Product	Size	Part #	Description
222MS	10ml	22221	Easy removal for screws under 1/4"
222	50ml	21464	Lower strength for screws under 1/4"
242	10ml	24221	Removable grade, 1/4" to 3/4" bolts
	50ml	24231	
	250ml	24241	
243	10ml	1329837	Primerless, 1/4" to 3/4" bolts
	50ml	1329467	Light oil contamination
	250ml	1329505	
248	9gr	37684	Medium Strength Semisolid Stick Blue
	19gr	37087	
262	10ml	26221	High Strength
	50ml	26231	
	250ml	26241	
263	10ml	1330583	High Strength, Primerless, 1/4" to 3/4" bolts
	50ml	1330585	Light oil contamination
	250ml	1350335	
268	9gr	37685	High Strength Semisolid Stick Red
	19gr	37686	
271	10ml	27121	High Strength up to 1" bolts
	50ml	27131	
272	50ml	27240	High Strength, High Temp to 450°F
277	50ml	27731	Permanent for bolts >7/8"
290	10ml	29021	Wicking grade for pre assembled parts
	50ml	29031	

Loctite Liquid Thread Sealants

Henkel



Loctite Liquid Thread Sealants seal and secure metal pipes and fittings, filling the space between threaded metals parts, and hardening to prevent leakage.

Product	Size	Part #	Description
565	50ml	56531	Controlled Strength
	250ml	56541	
567	50ml	56747	For Stainless, aluminum and all other fittings
	250ml	56765	
592	50ml	59231	Medium Strength
	250ml	59241	
545	50ml	54531	Hydraulic, Pneumatic Sealant
	250ml	54541	

Loctite Instant Adhesives

Henkel



Loctite brand instant adhesives are available in a variety of viscosities, cure speeds, gap filling capabilities, and substrate compatibilities.

Product	Size	Part #	Description
380	1oz	38050	Elastomer modified, bonds rubber, metal & plastic
401	20gr	40140	Surface Insensitive low viscosity
404	1/3oz	46551	Rubber o-ring bonder
409	20gr	40945	General Purpose Gel
411	3gr	41104	Gap Filling
420	1oz	42050	Wicking type plastic bonder
422	1oz	42250	Gap Filling plastic bonder
454	3gr	45404	Gel, porous surfaces
495	3gr	49504	General Purpose
	1oz	49550	
496	1oz	49650	General purpose rubber bonder



ADHESIVES & CAULKING



Loctite 515 Gasket Eliminator Flange Sealant

Henkel

This anaerobic gasketing material is well suited for rigid machined flanges that move in service. Fills gaps up to 0.50" and 300° F.

Part #	Size
51531	50ml



Loctite 609 Retaining Compound - General Purpose

Henkel

A low viscosity retaining compound that bonds rigid metal assemblies. Ideal for gap distances up to 0.006" diametral. Fixtures in 10 minutes and provides a shear strength of 3000psi after 24 hours. Withstands temperatures to 300° F.

Part #	Size
60931	50ml



Loctite 587 Blue High Performance RTV Silicone Gasket Maker

Henkel

Forms tough, flexible gaskets directly on the flange. Offers excellent adhesion to oily surfaces. Low odor, noncorrosive, low volatility. Resistant to most chemicals and solvents. Withstands temperatures up to 500° F intermittent. Fills gaps up to 0.25".

Part #	Size
58775	300ml
58730	70ml tube



Loctite Natural Blue Biodegradable Cleaner and Degreaser

Henkel

Biodegradable, all purpose, industrial strength, concentrated cleaner and degreaser. Can be economically diluted with water. Formulated for wipe down, pressure spraying and immersion cleaning processes at room temperature or heated. Non-flammable and non-toxic.

Part #	Size
82251	1 gallon

Loctite 680 High Strength/High Viscosity Retaining Compound

Henkel



A high strength high viscosity room temperature curing adhesive used to join fitted cylindrical parts. Provides a shear strength up to 4000psi and fills diametral gaps up to 0.015".

Part #	Size
68035	50ml

Loctite Instant Gasket

Henkel



Makes high-performance, leakproof gaskets in one minute. Equipment can be returned to service immediately. Blowout resistant. Outperforms pre-cut gaskets.

Part #	Size
40479	190ml can

Loctite 330 Depend Adhesive

Henkel



A general-purpose, high viscosity adhesive for a wide range of materials including metal, wood, ferrite, ceramic and plastic.

Part #	Size
20251	25ml kit



ADHESIVES & CAULKING

3600EX Intumescent Firestop Caulking



3600EX is a latex-based, highly intumescent (expands up to 8x) one-component product designed and tested to firestop through-penetrations, voids and construction joints.

Packaging	Colour
10 fl. oz. (300 ml) cartridge	Rust Red
20 fl. oz. (600 ml) foil sausage pack	Rust Red
29 fl. oz. (850 ml) cartridge	Rust Red
5 us gal. (18.9 L) pail (tapered)	Rust Red

4100NS Non-Sag Firestop Caulking



4100NS is a latex-based, one-component non-sag firestop sealant designed and tested predominately for firestopping construction joints.

Packaging	Colour
10 fl. oz. (300 ml) cartridge	Grey
20 fl. oz. (600 ml) foil sausage pack	Grey
29 fl. oz. (850 ml) cartridge	Grey
5 us gal. (18.9 L) pail (tapered)	Grey

4100SL Self-Leveling Firestop Caulking



4100SL is a one-component, latex-based self-leveling firestop sealant product designed and tested for firestopping through-penetrations of horizontal assemblies and construction joints.

Packaging	Colour
29 fl. oz. (850 ml) cartridge	Rust Red
35.2 fl. oz. (1 L) EZ pour plastic bottle	Rust Red
2.65 us gal (10 L) plastic pail	Rust Red
5 us gal. (18.9 L) pail (tapered)	Rust Red

4800DW Endothermic Firestop Caulking



4800DW is a latex-based, one-component endothermic firestop sealant product designed and tested to firestop through-penetrations, voids and construction joints.

Packaging	Colour
10 fl. oz. (300 ml) cartridge	Rust Red
20 fl. oz. (600 ml) foil sausage pack	Rust Red
29 fl. oz. (850 ml) cartridge	Rust Red
5 us gal. (18.9 L) pail (tapered)	Rust Red

5100SP Endothermic Firestop Spray



5100SP is a latex-based, endothermic firestop mastic designed and tested to firestop through-penetrations, construction joints and perimeter containment assemblies.

Packaging	Colour
5 us gal. (18.9 L) pail (tapered)	Grey

MP1 Firestop Intumescent Putty Pads



MP1s are a moldable intumescent firestop pad designed to be easily installed to metallic and non-metallic electrical outlet boxes. Designed specifically to seal electrical switches and outlet boxes against the spread of fire, smoke, fumes and toxic gases in 1 and 2 hour rated assemblies.

Packaging	Colour
7-1/4 inches by 7-1/4 inches by 1/8 inches (178 mm by 178 mm by 3.2 mm)	Dark Red
	Dark Red

PPC Collar Plastic Pipe Collar



PPC Collars are made with a durable one-piece powder coated steel case that contains intumescent strips designed to firestop combustible pipes. In the case of a fire, the collar's intumescent strips expand to constrict combustible pipe.

Packaging	Colour
PPC 1.5 – 1-1/2 inch (38 mm)	Red
PPC 2.0 – 2 inch (51 mm)	Red
PPC 3.0 – 3 inch (75 mm)	Red
PPC 4.0 – 4 inch (101 mm)	Red
PPC 6.0 – 6 inch (152 mm)	Red

WS1 Intumescent Wrap Strip



The highly intumescent wrap strips is a flexible fiberglass backed strip, designed to firestop combustible pipes and insulated pipe penetrations. In the case of a fire, the intumescent strips expand to constrict and close off combustible pipes.

Packaging	Colour
2 inch by 40 foot (51mm by 12.2m) rolls	Grey



ADHESIVES & CAULKING

NuFlex® 302 Bath & Kitchen (B & K) Silicone Sealant



NuFlex® 302 Bath & Kitchen has good resistance to weathering, vibration, moisture, ozone and extreme temperatures. It may be applied in sub-zero weather without loss of extrusion or physical property characteristics and is effective to -46°C (-50°F).

Part #	Size	Description
NUC30240	300ml	Sanitary Silicone Clear
NUC30241	300ml	Sanitary Silicone White
NUC30248	300ml	Sanitary Silicone Trans

NuFlex® 302 Hi-Temperature (HT) Silicone Gasket Maker



NuFlex® 302 HT was formulated to perform at temperatures ranging from -65°C to 260°C (-85°F to 500°F) under continuous operating conditions. During intermittent exposure, NuFlex® 302 HT will withstand temperatures as high as 316°C (600°F). It is ideal for a number of sealing and bonding applications.

Part #	Size	Description
NUC30209-BLK	83ml Squeeze	Silicone High Heat Black
NUC30209-RED	300ml	Silicone High Heat Red

NuFlex™ 302 General Purpose (GP) Silicone Sealant



NuFlex® 302 GP is a medium modulus, one component caulking material with a consistency similar to toothpaste. It cures to form a tough, rubbery solid through exposure to moisture in the air. NuFlex® 302 GP can be easily used for ceiling and sidewall applications without the fear of sagging, slumping or running off the application.

Part #	Size	Description
NUC30280	83ml Squeeze	Silicone Clear
NUC30281	83ml Squeeze	Silicone White
NUC30283	83ml Squeeze	Silicone Black

NuFlex® 446 Acoustical & Vapour Barrier Sealant



NuFlex® 446 Acoustical & Vapour Barrier Sealant is specially formulated to adhere to most common vapour barrier films as well as wood, metal, concrete and foam boards. NuFlex® 446 is non-skinning and non-hardening. A permanently flexible non-slumping sealant.

Part #	Size	Description
NUC44680	825ml	Acoustical Sealant

NuFlex® 180 Tub & Tile



NuFlex® 180 Tub & Tile is an excellent all-purpose sealant for cracks and joints and exhibits good adhesion to the full range of construction substrates such as: wood, concrete, metal, glass, stone, brick, stucco and marble. It is also recommended for sealing interior joints between walls and panels, around door frames and baseboards and joints between bathroom fixtures and walls.

Part #	Size	Description
NUC18060	162ml Squeeze	Tub & Tile Caulk Clear
NUC18061	162ml Squeeze	Tub & Tile Caulk White

NuFlex® 454 General Purpose Construction Adhesive



Ideal for interior and exterior applications, NuFlex® 454 General Purpose Construction Adhesive provides excellent water-resistance when cured and works well in colder temperatures. It also offers a 20 minute working time to allow precise placement of materials.

Part #	Size	Description
NUC45400	300ml	Foam Board Adhesive



ADHESIVES & CAULKING

NuFlex® 458 All Weather Subfloor Adhesive



NuFlex® 458 All Weather Subfloor Adhesive fills gaps and irregularities between materials and provides a more solid backup surface. It reduces the amount of nailing, increases floor rigidity and helps eliminate squeaky floors. NuFlex® 458 works extremely well in colder temperatures and offers excellent water-resistance.

Part #	Size	Description
NUCF458LRG	825ml	Sub-Floor Adhesive

G1 & G2 Professional Foam Guns



G1 Professional dispensing foam gun is for use with our gun dispensed UltraSeal® foaming systems. The G1 is a heavy duty gun that provides durability, high yield and total control.

The **G2 Professional** Dispensing Foam Gun is an intermediate steel gun that provides application control at a reasonable cost. The G2 Foam Gun features a flow control valve for bead adjustment. It is an excellently constructed gun that provides durability and total control. Its partial steel construction withstands the everyday abuse that can be found on construction sites.

The G2 Professional Dispensing Foam Gun is not rebuildable.

Part #	Description
NUC99321	Foam Gun G-1 H/Duty
NUC99354	Foam Gun G-2 Med Duty

NuFlex® 128 Caulking Gun



The NuFlex 128 is a premium gun with all the features the professional demands. Strong, yet lightweight all steel construction, full sized contoured handle for precision and comfort. Designed for easy loading of 28.8 fl oz (850ml) caulking tubes. The NuFlex 128 is easy to use with features like the thumb action lever for dispensing control, as well as a nozzle clearing needle.

Part #	Description
NUC128	1/4 Gal Caulking Gun

UltraSeal® PF-50 Extreme Weather Straw Foam



New Formulation! UltraSeal® PF-50 Extreme Weather Straw Foam is a low expansion, one-component polyurethane foam that is UL classified and designed to be used with a straw dispenser. It is ideal for general sealing of gaps, holes and crevices in EXTREME temperature conditions all year round. UltraSeal® PF-50 is a foam system that can be used without a gun dispenser.

Part #	Size	Description
NUC70300	12oz	Foam Spray PF50
NUC70600	24oz	Foam Spray PF50

UltraSeal® PF-120 Window and Door Foam



UltraSeal® PF-120 Window and Door Foam's low pressure feature greatly reduces the chance of bowing windows and doors while curing. It forms a superior air seal which prevents heat loss, noticeable drafts and is ideal for a variety of application areas. UltraSeal® PF-120 can be easily installed using any one of NUCO's dispensing foam guns.

Part #	Size	Description
NUC71024	24oz	Foam Gun / Window & Door

UltraSeal® PF-100 All Weather



UltraSeal® PF-100 All Weather Gun Foam's low expansion feature greatly reduces the time for post cure clean up and trimming if installed correctly. It forms a superior air seal which prevents heat loss, noticeable drafts and is ideal for a variety of application areas in EXTREME weather conditions all year round. UltraSeal® PF-100 All Weather adheres to many substrates and can be easily installed with any one of NUCO's dispensing foam guns.

Part #	Size	Description
NUC71600	24oz	Foam Gun PF-100

UltraSeal® PF-10 Foam Cleaner



UltraSeal® PF-10 Foam Cleaner is a cleaning solvent used to dissolve any uncured foam and adhesive foam from unwanted places. Uniquely designed for use with the NUCO dispensing guns. UltraSeal® PF-10 will work for general cleaning purposes as well.

Part #	Size	Description
NUC73400	12oz	Gun Foam Cleaner



ADHESIVES & CAULKING

Dow GREAT STUFF PRO™ Gap & Cracks



- First polyurethane foam product recognized as an alternative FIREBLOCKING material for combustible construction (residential and commercial).
- Orange-colored foam is easily identifiable to code officials
- Easier and faster to apply than other approved materials
- Low cost to builders
- Peace-of-mind to homeowners; it's a name they can trust
- International Code Council Evaluation Service recognizes – ESR-1961 GREAT STUFF Proas an acceptable alternative fireblocking material

Catalog ID Size
DOW342101 24oz

Dow GREAT STUFF PRO™ Gun Cleaner



- GREAT STUFF PRO™ Gun Cleaner helps keep PRO Series foam dispensing guns and other Spray Guns at their best.
- Uniquely formulated to dissolve and remove uncured polyurethane foam
- GREAT STUFF PRO™ Gun Cleaner makes application and cleanup simple.

Catalog ID Size
DOW218436 12oz

Dow GREAT STUFF PRO™ Window & Door



- Stop unwanted drafts and moisture intrusion around window and door frames
- Proprietary low pressure formulation
- Proven not to distort or bow window and door frames
- Saves builders time and money
- Improves home energy efficiency

Catalog ID Size
DOW217041 20oz

Dow GREAT STUFF PRO™ 13 Gun



- Applicator tool available in 26" extended barrel for: sub-floor applications – saves installer from back strain
- Ergonomically friendly
- Three styles to choose from
- Solid construction
- Easy to clean/maintain
- Restart up to 30 days
- Positive shut off at tip
- Variable bead adjustment
- Consistent bead size & precise control
- Unique mechanical valve won't glue shut

Catalog ID Size
DOW230408

Dow GREAT STUFF PRO™ Wall & Floor Adhesive



- Improves quality of wall construction
- Minimizes squeaky floors and stairs
- Significantly more cost effective than caulk adhesives

Catalog ID Size
DOW343088 26.5oz

Dow GREAT STUFF PRO™ 14 Gun



- Applicator tool available in 26" extended barrel for: sub-floor applications – saves installer from back strain
- Ergonomically friendly
- Three styles to choose from
- Solid construction
- Easy to clean/maintain
- Restart up to 30 days
- Positive shut off at tip
- Variable bead adjustment
- Consistent bead size & precise control
- Unique mechanical valve won't glue shut

Catalog ID Size
DOW230409



ADHESIVES & CAULKING

Dow GREAT STUFF PRO™ Work Wipes



- Durable, tear-resistant
- No harsh solvents
- Pleasant citrus scent
- No additional rags required
- Conveniently fit in toolbox/tool belt

Catalog ID Size

DOW359308

Dow GREAT STUFF PRO™ Froth Pak 200



FROTH-PAK™ Foam Sealant is a two-component, quick-cure polyurethane foam that fills cavities, penetrations, cracks and expansion joints. FROTH-PAK™ Foam Sealant can also be used as a sealant and void fill in many roofing applications. FROTH-PAK™ is a chemically cured foam, which significantly reduces curing time. FROTH-PAK™ dispenses, expands and becomes tack-free in seconds. It skins over in 30-40 seconds and completely cures in minutes, depending on temperature.

Catalog ID Size

DOW364724

Butyl Glazing Tape



Tremco 440 Tape is a 100% solid Polyisobutylene cross-linked butyl, preformed sealant.

Basic Uses

Tremco 440 Tape is used for non-compression glazing of vision lites and spandrel panels in PVC metal and wood frames, in low rise building construction. Also used for lap sealing between panels such as steel, aluminum and porcelain as well as a variety of other joints subject to shear between similar and dissimilar materials.

Size

1/16, 1/8, 3/16, 1/4" THICKNESS
1/4 – 1" WIDTH

Colours

Aluminum, Black
Aluminum, Black

General Purpose Butyl Sealant



Tremco Butyl Sealant is formulated from a blend of butyl rubber and polyisobutylene to form an economical, flexible sealant.

Basic Uses

Tremco Butyl Sealant is used for sealing joints in applications such as curtainwall joints, metal panel joining, bedding thresholds, secondary glazing seals, and areas where a seal is required against Tremco Neoprene or EPDM gaskets.

Size

1/16, 1/8, 3/16, 1/4" THICKNESS
1/4 – 1" WIDTH

Colours

Aluminum, Black
Aluminum, Black