

Quiet Composite Impact 3/8" (10 mm) - 1/2" (13 mm) - 3/4" (19 mm)



- Friction Ring Socket Retainer
- Reverse bias motor
- Twin hammer impact mechanism
- Three Level power control
- Lightweight composite housing
- Contoured trigger for comfort and control

3/8" (10mm) SPECS

- Grade 5 bolt capacity: 3/8" (10 mm)
- Torque: 100-180 ft/lbs (135-245 Nm)
- Max. torque: 250 ft/lbs (339 Nm)
- Free speed: 9000 RPM
- Blows per minute: 900
- Air inlet size: 1/4" NPT
- Low sound level 85 dB (A)
- Average Air consumption: 2.8 cfm (1.3 l/s)



1/2" (13mm) SPECS

- Grade 5 bolt capacity : 5/8" (16 mm)
- Torque : 100 - 450 ft./lbs. (135 - 610 Nm)
- Max. torque : 520 ft.lbs. (705 Nm)
- Free speed : 6300 RPM
- Blows per minute : 1200
- Air inlet size : 1/4" NPT
- Low sound level 82 dB (A)
- Average Air consumption : 3.9 cfm (1.8 l/s)



3/4" (19mm) SPECS

- Grade 5 bolt capacity: 3/4" (19 mm)
- Drive Size: 3/4"
- Torque: 300 - 800 ft/lbs. (407 - 1085 Nm)
- Max. torque: 1000 ft/lbs. (1356 Nm)
- Free speed: 4000 RPM
- Blows per minute: 300
- Air inlet size: 3/8" NPT
- Low sound level 82 dB (A)
- Average Air consumption: 5.6 cfm (2.6 l/s)

| Part # | Description | Weight (lbs.) |
|----------|--------------------------|---------------|
| SOT5338A | 3/8" Quiet Impact Wrench | 2.7 |
| SOT5350A | 1/2" Quiet Impact Wrench | 4.6 |
| SOT5375A | 3/4" Quiet Impact Wrench | 8.5 |

High Torque Impact Wrench 1" (25 mm) & 1" (25 mm) "D" Handle



- Pin impact mechanism
- Oil bath lubrication
- Support handle
- Friction Ring and Thru hole socket retainer
- Grade 5 bolt capacity: 1-1/2" (38 mm)
- Drive size: 1" (25 mm)
- Torque: 600-1400 ft lb (813-1898 Nm)
- Free speed: 4000 rpm
- Blows per minute: 500
- Air Consumption: 8.3 cfm (235 l/s) avg. – 33.2cfm (938 l/s) max.

1" (25mm) SPECS

- Max. torque: 2800 ft lb (3797 Nm)

1" (25mm) "D" Handle SPECS

- Max. torque: 3000 ft lb (4068 Nm)

| Part # | Description | Weight (lbs.) |
|---------|-----------------------------|---------------|
| SOT5092 | 1" Impact Wrench | 24.9 |
| SOT5093 | 1" "D" Handle Impact Wrench | 25.6 |

Medium Duty Die Grinder



- Lockoff lever throttle • Speed regulator
- Rear exhaust • Aluminum housing
- Power: 0.5 hp (0.4 kw)
- Free speed: 22,000 rpm
- Collet size: 1/4" • Air inlet: 1/4" NPT
- Air Consumption: 4.0 cfm (113 l/s) avg. – 16.0 cfm (452 l/s) max.

| Part # | Description | Weight (lbs.) |
|----------|-------------------------|---------------|
| SOT5054A | Medium Duty Die Grinder | 1.3 |

Heavy Duty Right Angle Die Grinder



- Lockoff lever throttle
- Rear Exhaust • Speed regulator
- Power: 0.5 hp (0.4 kw)
- Free speed: 16,000 rpm
- Collet size: 1/4" • Air inlet: 1/4" NPT
- Head Height: 3.0" (76 mm)
- Air Consumption: 4.5 cfm (127 l/s) avg. – 18.0 cfm (508 l/s) max.

| Part # | Description | Weight (lbs.) |
|---------|-------------------------|---------------|
| SOT5056 | Right Angle Die Grinder | 2.0 |

Medium Duty Air Hammer



- Spring retainer • Air Regulator
- Accepts .401 Parker Taper shanks
- Hardened steel barrel and piston
- Aluminum pistol-grip housing
- Stroke length: 3.8" (97 mm)
- Bore diameter: 0.8" (20 mm)
- BPM: 2200 • Air inlet: 1/4" NPT

| Part # | Description | Weight (lbs.) |
|----------|-------------|---------------|
| SOT5274A | Hammer | 4.7 |

Reciprocating Air Saw



- Comfort Grip Handle
- SPM: 10,000 • Adjustable Blade Guard
- Lockoff lever throttle • Air inlet: 1/4" NPT
- Built-in speed regulator

| Part # | Description | Weight (lbs.) |
|----------|---------------|---------------|
| SOT5300A | Recip Air Saw | 1.8 |

Cut-off Tool



- Rear exhaust • Comfort Grip
- Lockoff lever throttle
- Aluminum housing
- Free speed: 21,000 rpm
- Wheel size: 3.0" (76 mm)
- Air inlet size: 1/4" NPT

| Part # | Description | Weight (lbs.) |
|----------|-----------------|---------------|
| SOT5564A | 3" Cut-off Tool | 1.8 |

Pneumatic Drill - 3/8" (10 mm)



- Keyed chuck • Reversible
- Aluminum housing
- Chuck capacity 3/8" (10 mm)
- Free speed: 1800 rpm
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- 3/8" - 24 Spindle thread

| Part # | Description | Weight (lbs.) |
|----------|----------------|---------------|
| SOT5445R | 3/8" Air Drill | 3.0 |

Pneumatic Drill - 1/2" (13 mm)



- Keyed chuck • Reversible
- Aluminum housing • Support handle
- Free speed: 550 rpm • 1/2" - 20 Spindle
- Chuck capacity: 1/2" (13 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)

| Part # | Description | Weight (lbs.) |
|----------|----------------|---------------|
| SOT5450R | 1/2" Air Drill | 4.3 |

Right Angle Drill - 3/8" (10 mm)



- Keyed chuck • Reversible
- Aluminum housing • Rear exhaust
- Built-in speed regulator
- Free speed: 1200 rpm • 3/8" - 24 Spindle
- Chuck capacity: 3/8" (10 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)

| Part # | Description | Weight (lbs.) |
|------------|----------------------------|---------------|
| SOTFDR5430 | 3/8" Right Angle Air Drill | 2.5 |

Ratchet Wrench - 1/4" (6 mm)



- Steel angle head • Aluminum housing
- Ergonomic Composite Grip
- Grade 5 bolt capacity: 5/16" (8 mm)
- Drive size: 1/4" (6 mm)
- Maximum torque: 20 ft lb (27 Nm)
- Free speed: 265 rpm • Air inlet: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Air Consumption: 1.2 cfm (37 l/s) avg. - 5.2 cfm (147 l/s) max.

| Part # | Description | Weight (lbs.) |
|---------|---------------------|---------------|
| SOT5009 | 1/4" Ratchet Wrench | 1.5 |

Ratchet Wrench - 3/8" (10 mm)



- Steel angle head
- Aluminum housing
- Ergonomic Composite Grip
- Grade 5 bolt capacity: 7/16" (11 mm)
- Drive size: 3/8" (10 mm)
- Maximum torque: 50 ft lb (68 Nm)
- Free speed: 185 rpm
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Air Consumption: 3.0 cfm (85 l/s) avg. - 12.0 cfm (340 l/s) max.

| Part # | Description | Weight (lbs.) |
|---------|---------------------|---------------|
| SOT5011 | 3/8" Ratchet Wrench | 2.6 |

Ratchet Wrench - 1/2" (13 mm)



- Steel angle head
- Aluminum housing
- Ergonomic Composite Grip
- Grade 5 bolt capacity: 7/16" (11 mm)
- Drive size: 1/2" (13 mm)
- Maximum torque: 50 ft lb (68 Nm)
- Free speed: 185 rpm • Air inlet: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Air Consumption: 3.0 cfm (85 l/s) avg. - 12.0 cfm (340 l/s) max.

| Part # | Description | Weight (lbs.) |
|---------|---------------------|---------------|
| SOT5013 | 1/2" Ratchet Wrench | 2.6 |

Butterfly Impact Wrench - 3/8" (10 mm)



- Power regulator • Swivel air inlet bushing
- Friction ring socket retainer
- Grade 5 bolt capacity: 3/8" (10 mm)
- Drive size: 3/8" (10 mm)
- Torque range: 15-160 ft lb (20-217 Nm)
- Max. torque: 175 ft lb (237 Nm)
- Free speed: 9500 rpm
- Blows per minute: 1850
- Air inlet: 1/4" NPT
- Air Consumption: 2.5 cfm (1.2 l/s) avg.

| Part # | Description | Weight (lbs.) |
|---------|--------------------|---------------|
| SOT5045 | 3/8" Impact Wrench | 2.5 |

Impact Wrench 3/8" (10 mm) - 1/2" (13 mm) - 3/4" (19 mm)



- Reverse bias power • Oil bath lubrication
- Pin style impact mechanism
- Built-in power regulator • Comfort grip
- Friction ring socket retainer
- Air inlet: 1/4" NPT • Air Consumption: 3.5 cfm (100 l/s) avg. - 14.0 cfm (395 l/s) max.

3/8" (10mm) SPECS

- Grade 5 bolt capacity: 3/8" (10 mm)
- Drive size: 3/8" (10 mm)
- Working torque: 50-160 ft lb (68-217 Nm)
- Max. torque: 185 ft lb (251 Nm)
- Free speed: 8500 rpm • BPM: 1160



1/2" (13mm) SPECS

- Grade 5 bolt capacity: 5/8" (16 mm)
- Drive size: 1/2" (13 mm)
- Working torque: 50-375 ft lb (68-508 Nm)
- Max. torque: 525 ft lb (712 Nm)
- Free speed: 7000 rpm • BPM: 985



3/4" (19mm) SPECS

- Grade 5 bolt capacity: 3/4" (19 mm)
- Drive size: 3/4" (19 mm)
- Working torque: 300-800 ft lb (34-1084 Nm)
- Max. torque: 1200 ft lb (1627 Nm)
- Free speed: 4500 rpm
- Blows per minute: 870

| Part # | Description | Weight (lbs.) |
|----------|--------------------|---------------|
| SOT5038B | 3/8" Impact Wrench | 3.7 |
| SOT5250A | 1/2" Impact Wrench | 6.0 |
| SOT5075A | 3/4" Impact Wrench | 12.6 |

.33 hp Pistol Grip Drill - 1/4" (6 mm)



- Reversible, Trigger Start
- Rubber Grip
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 1/4" (6 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • 3-jaw Chuck and Key • Comfort Grip



| Part # | Description | Weight (lbs.) |
|----------|--------------------------|---------------|
| SOT1410R | 1/4" Air Drill, 2000 RPM | 1.3 |

1 hp Pistol Grip Drill - 3/8" (10 mm)




- Reversible, Trigger Start
- Rubber Grip
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 1/4" (6 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • 3-jaw Chuck and Key • Comfort Grip



| Part # | Description | Weight (lbs.) |
|---------------|--------------------------|---------------|
| SOTSDR10P25R3 | 3/8" Air Drill, 2500 RPM | 2.6 |

1 hp Right Angle Drill - 3/8" (10 mm)



- 90° Angler Head • Reversible • Lever Start
- Heads can be rotated 360°
- Rear or Side Exhaust
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • 3-jaw Chuck and Key



| Part # | Description | Weight (lbs.) |
|---------------|--------------------------|---------------|
| SOTSDR10A20R3 | 3/8" Air Drill, 2000 RPM | 3.0 |

ADJUSTABLE CLUTCH / POSITIVE CLUTCH / STALL SCREWDRIVERS

Over 100 Adjustable Clutch / Positive Clutch / Stall models available for whatever your application requires



- Reversible, Trigger Start
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 1/4" (6 mm) (10M series); 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Comfort Grip • Clutch Adjustment Wrench



| Part # | Description | Weight (lbs.) |
|---------------|-----------------------------|---------------|
| SOTSSD10P20AC | 80 in. lb. Torque, 2000 RPM | 2.8 |

Right Angle Screwdrivers



- Reversible, Lever Start
- Shuttle Reverse • Rear Exhaust
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 1/4" (6 mm) (10M series); 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure • Comfort Grip



| Part # | Description | Weight (lbs.) |
|--------------|------------------------------|---------------|
| SOTSSD10A10S | 145 in. lb. Torque, 1000 RPM | 3.4 |

Right Angle Nutrunner - 5/16" (8 mm)



- Reversible • Stall Drive • Lever Start
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 1/4" (6 mm) (10M series); 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Comfort Grip (1AM series) • Clutch Adjustment Wrench • Rear Exhaust



| Part # | Description | Weight (lbs.) |
|--------------|------------------------------|---------------|
| SOTSNR10A10S | 145 in. lb. Torque, 1000 RPM | 2.9 |

Impact Wrench - 3/8" (10 mm)



- Pistol Grip • Steel Anvil Housing
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Suspension Bail
- Square drive



| Part # | Description | Weight (lbs.) |
|---------------|------------------------|---------------|
| SOTIW38HAP-3F | Max Torque 250 ft. lb. | 3.3 |

Impact Wrench - 1/2" (13 mm)



- Pistol Grip • Steel Anvil Housing
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Suspension Bail
- Square drive



| Part # | Description | Weight (lbs.) |
|---------------|------------------------|---------------|
| SOTIW50HAP-4F | Max Torque 550 ft. lb. | 4.3 |

Impact Wrench - 3/4" (19 mm)



- Pistol Grip • 1000 BPM
- Steel Anvil Housing
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Suspension Bail



| Part # | Description | Weight (lbs.) |
|--------------|-------------------------|---------------|
| SOTIW75BP-6H | Max Torque 1000 ft. lb. | 11.6 |

1 hp Straight Die Grinder



- Lever Throttle • Speed Control • 78 dB
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Collet & Wrenches



| Part # | Description | Weight (lbs.) |
|--------------|----------------|---------------|
| SOTSDG10S25F | Max RPM 25,000 | 1.7 |

1 hp Right Angle Die Grinder



- Lock-off Lever • Speed Control • 78 dB
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Collet & Wrenches

| Part # | Description | Weight (lbs.) |
|-------------|----------------|---------------|
| SOTSAG10S18 | Max RPM 18,000 | 2.7 |

1 hp Right Angle Wheel Grinder



- Lock-off Lever Throttle
- Speed Control • 77 dB
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Collet & Wrenches

| Part # | Description | Weight (lbs.) |
|---------------|----------------|---------------|
| SOTSWG10S1245 | Max RPM 12,000 | 3.0 |

Material Removal Tool



- Removable Support Handle • Lockoff Lever
- Planetary Gear for Increased Torque
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Fine Belt (68813) • Course Belt (68814) • Eraser (68815) • Support Handle

| Part # | Description | Weight (lbs.) |
|-------------|--------------|---------------|
| SOTST2L1410 | Max RPM 4000 | 3.3 |

.25 hp Random Orbital Sanders

**MANY MODELS AVAILABLE
SEE YOUR SALES REP FOR DETAILS**



- Built-in Speed Control
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Comfort Grip • Backing Pad & Wrench

| Part # | Description | Weight (lbs.) |
|-----------------|----------------|---------------|
| SOTRO2512-50SNP | Max RPM 12,000 | 1.5 |

.40 hp Random Orbital Sanders



- 3/16" (5 mm) Orbit Diameter • Built-in Speed Control • Aluminum Housing • Lever Throttle
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Comfort Grip • Backing Pad & Wrench

| Part # | Description | Weight (lbs.) |
|--------|----------------|---------------|
| SOT658 | Max RPM 10,000 | 3.2 |

.45 hp Geared Orbital Sanders



- 3/16" (5 mm) Orbit Diameter
- Built-in Speed Control
- Lever Throttle • Non-Vacuum
- Ergonomic 24-Position Indexable Grip
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual

| Part # | Description | Weight (lbs.) |
|----------------|-------------|---------------|
| SOTGO459-60SNP | Max RPM 900 | 4.4 |

1 hp Pistol Grip Sander



- Trigger Start • Down-Handle Exhaust
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Comfort Grip

| Part # | Description | Weight (lbs.) |
|-------------|----------------|---------------|
| SOTSDG10P18 | Max RPM 18,000 | 1.7 |

.33 hp Right Angle Sander



- Lockoff Lever Throttle
- Front, Rear, and Vacuum Exhaust • Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Comfort Grip • Collet & Collet Wrenches (as required) • Angle Head Lubricant

| Part # | Description | Weight (lbs.) |
|-------------|----------------|---------------|
| SOT1DA221HP | Max RPM 20,000 | 1.2 |

1 hp Router (3" Base)



- Lockoff Lever Throttle
- Interchangeable Base • 1/4" Collet Size
- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety /Instruction Manual • Base/ Head Assembly, Collet, Collet Wrenches

| Part # | Description | Weight (lbs.) |
|---------|----------------|---------------|
| SOT1292 | Max RPM 25,000 | 2.6 |

1.5 hp Router - Twist Throttle (6" Dia.)



- Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
- Parts List • Safety and Instruction Manual • Base & Collet Wrenches

| Part # | Description | Weight (lbs.) |
|-----------|----------------|---------------|
| SOTRT1983 | Max RPM 20,000 | 4.8 |

Dynafile® II



- .5 hp, 20,000 RPM air motor.
- For use with 18" long abrasive belts.
- Grind & deburr with platen or blend & polish with belt slack.
- Lightweight, ergonomic 7° offset design.
- Grinding head pivots 360° for the most efficient position.
- Easily convert to a Die Grinder with optional 50010 Collet (1/4").
- Includes 11206 Contact Arm for 3/4" wide belts.

| Part # | Description |
|----------|-------------|
| DYT40320 | Air |

Electric Dynafile® II



- For use with 18" long abrasive belts.
- Runs coated abrasives and non-woven nylon belts.
- 11,000 RPM, and 120 V (AC) electric motor.
- Sanding head pivots 360°
- Reversible side handle for operator comfort.

| Part # | Description |
|----------|-------------|
| DYT40610 | Electric |

0.4 hp Die Grinder



- 25,000 RPM air motor.
- 7° Offset design with rear exhaust.
- Gearless for reduced maintenance and downtime.
- Includes 1/4" collet.

| Part # | Description |
|----------|-------------|
| DYT52204 | Air |

1.3 hp Depressed Center Wheel Grinder



- 4-1/2" Diameter, Right angle.
- 12,000 RPM, 5/8"-11 spindle thread.
- "Wick Lube" System extends gear life
- Tool accepts optional 4-1/2" diameter Type 27 Reinforced Depressed Center Wheels with 7/8" center hole.
- Includes wheel guard, backup flange and locking flange.

| Part # | Description |
|----------|-------------|
| DYT52632 | Air |

0.4 hp Pistol Grip Drill



- Ergonomic Dynabrade design, with comfortable textured tactile grip.
- 2,400 RPM powerful high-torque air motor is ideal for countless industrial applications.
- Finger platform on both sides of tool allows increased stability and comfort.
- Includes 1/4" Dynachuck.

| Part # | Description |
|----------|-------------|
| DYT52833 | Air |

Dynorbital® Silver Supreme



- Supreme power arrives in lightweight package!
- 12,000 RPM and a .26 hp air motor
- Steel cylinder and end plates stay perfectly aligned, to maximize motor performance!
- Non-vacuum model with a 3/16" diameter orbit for general sanding.
- 6" diameter low profile, premium urethane weight-mated sanding pad included.

| Part # | Description |
|----------|-------------|
| DYT69025 | Air |

Dynorbital-Spirit®



- Light-to-Medium duty sander with Dynabrade quality built in!
- 12,000 RPM and a .25 hp air motor
- Dynabrade's lightest Random Orbital Sander is ideal for vertical and contoured applications, and for operators with smaller hands.
- Non-vacuum model with a 3/16" diameter orbit for general sanding.
- 6" diameter low profile, premium urethane weight-mated sanding pad included.

| Part # | Description |
|----------|-------------|
| DYT59025 | Air |

Dynorbital® Supreme



- Setting the standard for random orbital supremacy!
- 12,000 RPM and a .28 hp air motor
- When operating on work surface, tool maintains highest RPM in the industry!
- Non-vacuum model with a 3/16" diameter orbit for general sanding.
- 6" diameter low profile, premium urethane weight-mated sanding pad included.

| Part # | Description |
|----------|-------------|
| DYT56826 | Air |

3/8" Standard Duty Reversible Pistol Grip Drill



- Hardened steel planetary gears for long life performance
- Excellent power to weight ratio
- Forward / Reverse switch conveniently located for one handed operation
- Contoured handle design and aluminum die cast throttle offer precise operator control
- Excellent for a wide range of drilling jobs.

| Part # | HP | RPM | Chuck (in.) | dBA |
|-----------|------|------|-------------|------|
| JET404415 | 0.33 | 2200 | 3/8 | 86.8 |

1/4" "Mini" Die Grinder - Standard Duty



- Quality advances for longer service life include: steel end plate inserts, brass collar, reinforced air inlet and cylinder made of higher quality steel
- All ball bearing construction for maximum tool life
- Lever throttle with roller for positive speed control
- Self-locking throttle lever prevents accidental starting of motor
- Built-in air regulator

| Part # | HP | RPM | Collet (in.) | dBA |
|-----------|-----|--------|--------------|-----|
| JET402109 | 0.3 | 25,000 | 1/4 | 2.5 |

1/4" Heavy Duty "Mini" Straight Die Grinder



- The combination of a mini length housing and a .6 horsepower motor make the MG1HD the most powerful and compact "mini" die grinder that JET offers
- Front exhaust two ball bearings construction, steel motor end plate motor housing made from aluminum dies cast for maximum service life
- Insulating vinyl cover for operator comfort and safety
- Lever throttle with roller tip for safety and ease of operation
- The ideal die grinder for maximum stock removal in confined areas Standard Accessories: Wrenches

| Part # | HP | RPM | Collet (in.) | dBA |
|-----------|-----|--------|--------------|-----|
| JET402114 | 0.6 | 20,000 | 1/4 | 95 |

1/4" Standard Duty "Mini" 90 Degree Angle Head Die Grinder



- Excellent for hard-to-get-at jobs that require flexibility in grinding
- Precise bevel gear systems reduces speed for powerful confined area work
- Featuring deeper cut gears locked in place by slot and pin mechanism for improved service life
- All ball bearing construction for maximum tool life
- Lever throttle for positive speed control
- Optional 1/8" collet sleeve included Standard Accessories: Wrenches, 1/8" collet

| Part # | HP | RPM | Collet (in.) | dBA |
|-----------|-----|--------|--------------|-----|
| JET402110 | 0.3 | 20,000 | 1/4 | 103 |

3/16" Air Riveter – Heavy Duty



- New improved model with powerful pulling load of 2,150 lbs
- Can be used on steel and aluminum rivets up to 3/16"
- The handle and cylinder are made using a special "low-pressure" casting process, significantly increasing strength and durability
- Longer 16mm stroke sets rivets in one hit, increasing efficiency
- Very compact and lightweight – only 3.08 lbs
- High grade, heat treated 3 piece jaw design
- Includes Nose piece- 3/32" (2.4mm), 1/8" (3.2mm), 5/32" (4.0mm), 3/16" (4.8mm)

| Part # | Capacity (in.) | Power (ft. - lbs.) | Inlet (in.) |
|-----------|----------------|--------------------|-------------|
| JET409001 | 3/16 | 2150 | 1/4 |

Heavy Duty Straight Type Flux Chipper



- A Powerful heavy duty industrial flux chipper
- Light-weight compact design allows maximum operator control and access to jobs in hard-to-reach areas
- Lever throttle control
- Easy to use ball type chisel retainer allows quick, easy bit changes
- Can be converted into needle scaler
- Ideal for all chipping operations including removal of slag, scale, welds and masonry Standard Accessories: 1" wide angle chisel (408402)

| Part # | BPM | Piston Dia. (in.) | Stroke (in.) |
|-----------|------|-------------------|--------------|
| JET404203 | 4500 | 1 | 7/8 |

Super Duty "Magnesium Series" Impact Wrench



- Twin hammer impact mechanism provides more power and smooth, balanced impact blows for reduced vibration
- Super strong magnesium housing – lighter and stronger than aluminum, magnesium absorbs impact vibration better than other materials, improving operator comfort and reducing fatigue
- Exceptionally well balanced tool, for comfort and ease of handling
- Ergonomic handle shaped to fit the operator's hand features: finger grooves for comfort and control; insulating and shock absorbing rubber cover extends to upper rear of handle to protect the web of the hand
- Exhaust air outlet features an effective muffler system for reduced noise in the work area • Handle exhaust directs air away from the operator and the work piece
- Forward/reverse control positioned for ease of use, three forward and one reverse setting
- Specially treated anvil for extra long service life
- A professional tool for professional users. Ideal for all automotive, industrial and farm service applications including truck, shock, frame, engine and spring work
- Maximum torque: Forward 550 ft.-lbs, Reverse 600 ft.-lbs

| Part # | BPM | Drive |
|-----------|------|--------|
| JET400245 | 4500 | Square |

Framing Nailers



28 Degree Wire Weld

| Part # | Description |
|------------|--------------------------------|
| BOSF28WW | 2"-3 1/2" 28 deg. Stick Framer |
| BOSS12D-FH | 3 1/4" x .120 Full Head |
| BOS10D-FH | 3" x .120 Coated |



33 Degree Paper Col.

| Part # | Description |
|-----------------|--------------------------------|
| BOSF33PT | 2"-3 1/2" 33 deg. Stick Framer |
| BOSPT-S12D120EP | 3 1/4" x .120 Coated |
| BOSPT-S10D120EP | 3" x .120 Coated |

Coil

| Part # | Description |
|------------------|---------------------------------|
| BOSN80CB-1 | 2" - 3 1/4" Coil Framing Nailer |
| BOSN89C-1 | 2" - 3 1/2" Coil Framing Nailer |
| BOSAC10D120-4.5M | 3" x .120 Coated Coil Nail |

Metal Connector Nailer & Nails



28 Degree Wire Weld

| Part # | Description |
|--------------------|--------------------------------|
| BOSMCN150 | 2"-3 1/2" 28 deg. Stick Framer |
| BOSPT-MC13115-1M | 1 1/2" x .131 Hangar Nail |
| BOSPT-MC13115GAL1M | 1 1/2" x .131 ACQ Hangar Nail |
| BOSPT-MC14815-1M | 1 1/2" x .148 Hangar Nail |

Prohose



28 Degree Wire Weld

| Part # | Description |
|--------------|----------------------|
| BOSPRO-1450 | 1/4" x 50' ProzHoze |
| BOSPRO-14100 | 1/4" x 100' ProzHoze |
| BOSPRO-3850 | 3/8" x 50' ProzHoze |
| BOSPRO-38100 | 3/8" x 100' ProzHoze |

Ask about the full range of Bostitch fittings and accessories!

Cordless - Nailers, Gas & Batteries



Nailers

| Part # | Description |
|-------------|--------------------------------------|
| BOSGF28WW | 2"-3 1/2" 28 deg. Stick Framer |
| BOSGF33PT | 2"-3 1/2" 33 deg. Stick Framer |
| BOSGBT1850K | 5/8" - 2" 18 Ga. Brad Nailer |
| BOSGFN1664K | 1" - 2 1/2" 16 Ga. Str. Finish Nails |
| BOSGFN1564K | 1 1/4" - 2 1/2" 15 Ga. Angle Finish |

Gas

| Part # | Description |
|-------------|-----------------------------|
| BOS9B12061R | Tall Red Framing, 2/Pck. |
| BOS9B12062R | Short Yellow Finish, 4/Pck. |

Sheathing Staplers & Staples



| Part # | Description |
|---------------|-----------------------------------|
| BOS650S4-1 | 16 Ga. Shtg. Stapler, 4.7 Lbs. |
| BOS750S4-1 | 16 Ga. Shtg. Stapler, 5.3 Lbs. |
| BOS16S4-31 | 16 Ga. 1/2" x 1 1/4" Brite Staple |
| BOS16S4-38 | 16 Ga. 1/2" x 1 1/2" Brite Staple |
| BOS16S4-31GAL | 16 Ga. 1/2" x 1 1/4" Galv. Staple |
| BOS16S4-38GAL | 16 Ga. 1/2" x 1 1/2" Galv. Staple |

Roofing Nailer & Nails



| Part # | Description |
|------------|---------------------------|
| BOSRN46-1 | Coil Roofing Nailer |
| BOSCR3DGAL | NAIL,COL,120,ROOF,1-1/4GA |
| BOSCR5DGAL | NAIL,COL,120,ROOF,1-3/4GA |

THE NEW GREX 2" 18 GAUGE BRAD NAILER THE BRAD NAILER YOU'VE BEEN WAITING FOR

1850GB
GREEN BUDDY™
2" 18 Gauge Brad Nailer

Long life and pressures up to 140psi with an all-metal body, internals and magazine - like industrial tools used to be made.



Jamming dramatically reduced by tighter tolerances and a bolt down nose cover.



Fire all day long and this depth of drive adjustment will not roll back.

Shoot at any angle with safety inside no-mar tip, which protects marring of work piece.



Fast recycle and switchable bump fire makes it a real production tool.

Add to all this a stepped magazine to access tight corners plus a large sighting window, rear exhaust swivel air coupler and a serious 2 year warranty and the package is complete.

2 Inch - 23 Gauge Headless Pinner



- Adjust-free magazine
- Auto Lock-out with reverse tank
- Double Trigger Safety
- Narrow Nose Design
- Removable nose cover
- Rear exhaust & silencer
- Fastener indicator window
- Convenient belt hook
- Swivel air coupler
- 2 year warranty

INCLUDES: Carrying case, safety goggles, oil bottle, wrenches, air coupler



| Part # | Capacities | Range | Gauge | Net Weight |
|-----------|------------|-----------|-------|------------|
| GREXP650L | 100 pins | 3/8" - 2" | 23 | 2.6 lbs. |

21 Gauge Stapler - Fine Wire (Auto Fire)



- Single fire and auto-fire
- auto-fire up to 18 staples/sec
- Slim profile & lightweight
- Powerful and fast air recycling
- Rear exhaust and silencer
- Easy pull-up magazine latch
- Steel head cap hammer
- Similar to BeA 80 series
- 2 year warranty

INCLUDES: Carrying case, oil bottle, wrenches, air coupler



| Part # | Capacities | Range | Gauge | Net Weight |
|----------|------------------|--------------|----------|------------|
| GREX80AF | 100 staples auto | 3/16" - 5/8" | 21 crown | 2 lbs. |
| GREX80AD | 100 staples | 3/16" - 5/8" | 21 crown | 2 lbs. |

1-3/16 Inch - 23 Gauge Headless Pinner



- Powerful motor
- Compact & lightweight
- Adjust-free magazine
- Double trigger safety
- Convenient side loading
- Narrow nose design
- Convenient belt hook
- 2 year warranty

INCLUDES: Carrying case, oil bottle, wrenches, air coupler



| Part # | Capacities | Range | Gauge | Net Weight |
|----------|------------|----------------|-------|------------|
| GREXP630 | 100 pins | 3/8" - 1-3/16" | 23 | 2.1 lbs. |

18 Gauge Stapler - Medium Wire (Crown)



- Powerful motor
- Depth of drive adjustment
- Tough aluminum die-cast body
- Quick release nose cover
- 360° adjustable exhaust cover
- Top drop in loading
- Rubber comfort hand grip
- 2 year warranty

INCLUDES: Carrying case, safety goggles, oil bottle, wrenches, air coupler



| Part # | Capacities | Range | Gauge | Net Weight |
|----------|-------------|----------------|-------|------------|
| GREX9040 | 150 staples | 1/2" - 1-9/16" | 18 | 4.2 lbs. |
| GREX9032 | 150 staples | 1-1/4" | 18 | 2.1 lbs. |

2-1/2" 16 Gauge Finish Nailer



- Depth of drive adjustment
- Tough aluminum die-cast-body
- Quick release nose cover
- Rubber comfort handgrip
- Convenient side loading
- Fastener indicator
- Rubber safety tip
- 360° adjustable exhaust cover
- 2 year warranty

INCLUDES: Carrying case, safety goggles, oil bottle, wrenches, air coupler



| Part # | Capacities | Range | Gauge | Net Weight |
|----------|------------|---------------|-----------|------------|
| GREX1664 | 100 nails | 3/4" - 2-1/2" | 16 finish | 4.7 lbs. |
| GREX1850 | 100 nails | 2" | 18 finish | ~ |

16 Gauge Staples - Heavy Wire



- Powerful motor
- Depth of drive adjustment
- Tough aluminum die-cast body
- Quick release nose cover
- 360° adjustable exhaust cover
- Rubber comfort hand grip
- Top drop in loading
- 2 year warranty

INCLUDES: Carrying case, safety goggles, oil bottle, wrenches, air coupler



| Part # | Capacities | Range | Gauge | Net Weight |
|----------|-------------|---------------|----------|------------|
| GREX1151 | 150 staples | 5/8" - 2" | 16 crown | 5.7 lbs. |
| GREX2638 | 150 staples | 5/8" - 1-1/2" | 16 crown | 5.7 lbs. |

Construction Stapler, Standard Crown, 7/16"



HITACHI
Inspire the Next

- 4.4lbs, lightweight & well balanced for easy maneuverability
- Exhaust muffler reduces noise pollution
- High capacity magazine holds 150 staples allowing for fewer replenishments
- Open magazine design allows users to quickly check staple quantity
- Quick-clear jam release increases user efficiency
- Plastic magazine with stainless steel plating adds durability
- Depth adjustment, to countersink or flush drive staples
- Long-lasting rubber grip, for added comfort
- Optional accessory: Single Trip Trigger Mechanism

INCLUDES:
Safety Glasses
Hex Bar Wrenches

| Part # | Description |
|-----------|-------------------------------|
| HITN5008A | 7/16" Stapler, Standard Crown |

Roofing Nailer, Coil, Wire Collation



HITACHI
Inspire the Next

- 5.5lbs, lightweight & well balanced for easy maneuverability
- Side loading magazine, convenient and easy for quick replenishment
- Tool-less depth of drive adjustment, for precision nailing/flush driving
- Carbide tipped push lever, reduces wear
- Rubber pads, help keep nailer from sliding off roof when not in use
- Quick driving, for maximum efficiency
- Pneumatic power feed and return, allows tool to operate in the harshest conditions

INCLUDES:
Safety Glasses
Hex Bar Wrenches

| Part # | Description |
|-------------|-----------------------------------|
| HITNV45AB2S | Bottom Load 5.7lbs Roofing Nailer |
| HITNV45AB2H | Power Pack 5.7lbs Roofing Nailer |

Full Round Head, Coil, Wire Collation



HITACHI
Inspire the Next

- 8.2lbs, lightweight and well balanced for easy maneuverability
- Quick driving, 2-valve, cylinder drive system for efficiency
- Top load pop-out magazine, easy to quickly replenish nails
- Hardened aggressive toenail push lever, resists wear for prolonged life
- Open nose design, for easy extraction of a jammed nail
- Plastic shield, for added safety

INCLUDES:
Safety Glasses
Hex Bar Wrenches
Tool Lubricant

| Part # | Description |
|-----------|---------------------------------------|
| HITNV83A2 | Full Round Head, Coil, Wire Collation |

2-1/2" 16-Gauge Finish Nailer with Air Duster



HITACHI
Inspire the Next

- 360 degree, fully adjustable exhaust port directs air exhaust away from the user during use
- 3.7 lbs, lightweight and well-balanced for minimal fatigue and increased maneuverability
- Accepts 1" to 2-1/2", 16-gauge fasteners

INCLUDES:
Safety Glasses
Hex Bar Wrenches
Case, No Mar Tip

| Part # | Description |
|-----------|--------------------------------|
| HITNT65M2 | 2 1/2", 16 Gauge Finish Nailer |

3-1/2" Clipped Head Framing Nailer"



HITACHI
Inspire the Next

- 7lbs, lightest weight in its class and well balanced for easy maneuverability
- Superior power, drives 3-1/2" .131 into eng. lumber.
- Selective actuation, allows for either sequential or contact nailing with the flip of a switch for tool-less transitions
- Two-piece anodized aluminum magazine, adds flexibility since either the magazine or mounting bracket can be repaired minimizing expense and eliminating unnecessary replacements
- Tool free depth of drive adjustment, for flush or countersunk drives into varying material.

INCLUDES:
Safety Glasses
Hex Bar Wrenches

| Part # | Description |
|-----------|------------------------------------|
| HITNR90AD | 3 1/2" Clipped Head Framing Nailer |

Utility Nailer, Light-Duty, Coil, Wire Collation



HITACHI
Inspire the Next

- 4.2lbs, lightweight & compact for easy maneuverability
- Angled magazine, permits nailing in tight spaces
- Open magazine canister, to quickly check nail quantity
- High capacity canister holds up to 400 nails
- Plastic shield, for added safety
- Optional accessory: Single Trip Trigger Mechanism

INCLUDES:
Safety Glasses
Hex Bar Wrenches

| Part # | Description |
|-----------|----------------------------|
| HITNV50A1 | Utility Nailer, Light Duty |

1-1/2" 18 Gauge Narrow Crown Stapler



HITACHI
Inspire the Next

- 2.2 lbs, lightweight and compact for easy use
- New selective actuation switch lets the user easily select bump fire or sequential fire modes
- 360 degree adjustable exhaust, can be directed away from user in any direction
- High-capacity magazine, holds up to 125 staples
- Tool-less, easy-to-clear nose, for quick and simple staple extraction
- Tool-less depth of drive, adjusts for flush or countersunk drives into varying material

INCLUDES:
Safety Glasses
Case
No-Mar Tipx2

| Part # | Description |
|-------------|---------------------------------------|
| HITN3804AB3 | 1 1/2", 18 Gauge Narrow Crown Stapler |

Angled Finish Nailer, 15-Gauge Angled Finish Nails



HITACHI
Inspire the Next

- 4.4lbs, lightweight and well balanced for ease of use
- Selective actuation (ANSI Compliant), allows transition from single actuation to contact actuation
- Depth adjustment, to countersink or flush drive nails
- Air duster, clears debris before material installation

INCLUDES:
Safety Glasses
Hex Bar Wrenches
Case, No Mar Tip

| Part # | Description |
|------------|----------------------------------|
| HITNT65MA2 | 15 Gauge Angled Finishing Nailer |

Full Head Framing Nailer



NEW



Quick Release Magazine

- Metal Strike Plate - Designed for positioning lumber and to take job-site abuse
- In-line Self-cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Single Action Follower Lock Back - Simple motion for loading and unloading nails
- Tool-less Adjustable Depth of Drive - Adjust depth of drive on tool
- Tool-less Selectable Trigger - Easily switch between bump and sequential fire

INCLUDES: Safety Glasses, No Mar Tip

| Part # | Angle | PSI | Capacity | Weight |
|--------------|-------|----------|----------|----------|
| BSTSN350-20F | 20° | 60 - 120 | 73 Nails | 8.4 lbs. |

Clipped Head Framing Nailer



NEW



Quick Release Magazine

- Metal Strike Plate - Designed for positioning lumber and to take job-site abuse
- Dry Fire Lock-out - Avoids damage to work materials and internal components by preventing blank firing
- In-line Self-Cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Single Action Follower Lock Back - Simple motion for loading and unloading nails
- Tool-less Adjustable Depth of Drive - Adjust depth of drive on tool
- Tool-less Selectable Trigger - Easily switch between bump and sequential fire

INCLUDES: Safety Glasses, No Mar Tip

| Part # | Angle | PSI | Capacity | Weight |
|--------------|-------|----------|----------|----------|
| BSTSN350-34C | 30° | 60 - 120 | 99 Nails | 8.4 lbs. |

Roofing Coil Nailer



NEW



Single Action Side Load

- Bosch Armor - Protects from job-site abuse and abrasive shingles
- In-line Self-Cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Dry Fire Lock-out - Avoids damage to work materials and internal components by preventing blank firing
- Tool-less Adjustable Depth of Drive - Adjust depth of drive on tool
- Tool-less Adjustable Shingle Guide - Enables user to change exposure dimension for different shingle types

INCLUDES: Safety Glasses, No Mar Tip

| Part # | Angle | PSI | Capacity | Weight |
|----------|-------|----------|-----------|----------|
| BSTRN175 | 15° | 75 - 120 | 100 Nails | 5.5 lbs. |

1/4" Narrow Crown Stapler - 18 Ga



Slim Body Better Line of Sight

15 Ga Angled Finish Nailer



NEW



Slim Body Better Line of Sight

- Dry Fire Lock-out - Avoids damage to work piece and internal components by preventing blank firing
- Tool-less Quick Clear - Easily remove jammed nails
- In-line Self-cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Tool-less Adjustable Depth of Drive - Adjust depth of drive at the tool
- Tool-less Adjustable Air Exhaust
- Tool-less Selectable Trigger - Easily switch operation between bump and sequential fire

INCLUDES: Safety Glasses, No Mar Tip, Carrying Case

| Part # | Angle | PSI | Capacity | Weight |
|--------------|-------|----------|-----------|----------|
| BSTFNA250-15 | 34° | 60 - 120 | 100 Nails | 4.0 lbs. |

16 Ga Straight Finish Nailer



NEW



Slim Body Better Line of Sight

- Dry Fire Lock-out - Avoids damage to work piece and internal components by preventing blank firing
- Tool-less Quick Clear - Easily remove jammed nails
- In-line Self-cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Tool-less Adjustable Depth of Drive - Adjust depth of drive at the tool
- Tool-less Adjustable Air Exhaust
- Tool-less Selectable Trigger - Easily switch operation between bump and sequential fire

INCLUDES: Safety Glasses, No Mar Tip, Carrying Case

| Part # | Angle | PSI | Capacity | Weight |
|--------------|----------|----------|-----------|----------|
| BSTFNS250-16 | Straight | 60 - 120 | 100 Nails | 3.5 lbs. |

18 Ga Brad Nailer



NEW



Slim Body Better Line of Sight

- Dry Fire Lock-out - Avoids damage to work piece and internal components by preventing blank firing
- Tool-less Quick Clear - Easily remove jammed nails
- In-line Self-cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Tool-less Adjustable Depth of Drive - Adjust depth of drive at the tool
- Tool-less Adjustable Air Exhaust
- Tool-less Selectable Trigger - Easily switch operation between bump and sequential fire

INCLUDES: Safety Glasses, No Mar Tip, Carrying Case

| Part # | Angle | PSI | Capacity | Weight |
|--------------|----------|----------|-----------|----------|
| BSTBNS200-18 | Straight | 60 - 120 | 100 Nails | 2.1 lbs. |

NEW

- Dry Fire Lock-out - Avoids damage to work piece and internal components by preventing blank firing
- Tool-less Quick Clear - Easily remove jammed nails
- In-line Self-cleaning Air Filter - Keeps debris away from the valve and o-rings, improving life of the tool
- Tool-less Adjustable Depth of Drive - Adjust depth of drive at the tool
- Tool-less Adjustable Air Exhaust
- Tool-less Selectable Trigger - Easily switch operation between bump and sequential fire

INCLUDES: Safety Glasses, No Mar Tip, Carrying Case

| Part # | Angle | PSI | Capacity | Weight |
|--------------|----------|----------|-----------|----------|
| BSTSTN150-18 | Straight | 60 - 120 | 100 Nails | 2.1 lbs. |

Electric Direct Drive 1 HP Air Compressor

ROLAIR



- 1 HP Electric Direct Drive
- 2.3 CFM @ 90 PSI
- Ultra-Quiet, Low-Speed Oilless
- 8 Amps

| Part # | Description | PSI | AMPS |
|---------|----------------------------|-----|------|
| ROLJC10 | 1 HP Electric Direct Drive | 90 | 8 |

Honda Belt Drive 5.5 HP Air Compressor

ROLAIR



- 5.5 HP Honda Belt Drive
- 9.3 CFM @ 90 PSI
- Automatic Engine Idle for Fuel Economy
- Schmidt Belt-Tightening Device

| Part # | Description | PSI | AMPS |
|-------------|----------------------------|-----|------|
| ROL4090HK17 | 5.5 HP Electric Belt Drive | 90 | - |

Electric Direct Drive 2 HP Air Compressor

ROLAIR



- 2 HP Electric Direct Drive
- 4.1 CFM @ 90 PSI
- Low-Profile Stack-Tank Design
- 13.8 Amps

| Part # | Description | PSI | AMPS |
|-----------|----------------------------|-----|------|
| ROLFC2002 | 2 HP Electric Direct Drive | 90 | 13.8 |

Electric Direct Drive 2 HP Air Compressor

ROLAIR



- 2 HP Electric Direct Drive
- 4.2 CFM @ 90 PSI
- Built-In Tool Box for Storage
- 12.3 Amps

| Part # | Description | PSI | AMPS |
|-----------|----------------------------|-----|------|
| ROLVT20TB | 2 HP Electric Direct Drive | 90 | 12.3 |

Electric Belt Drive 1.5 HP Air Compressor

ROLAIR



- 1.5 HP Electric Belt Drive
- 7.3 CFM @ 90 PSI
- Factory-Installed Dual-Voltage Motor
- 17 Amps

| Part # | Description | PSI | AMPS |
|------------|----------------------------|-----|------|
| ROL5715K17 | 1.5 HP Electric Belt Drive | 90 | 17 |

5 HP Stationary Air Compressor

ROLAIR



- 5 HP Stationary
- 16 CFM @ 100 PSI
- 1-Stage ~ 1 Phase Motor
- 60 Gallon CFN-Certified Tank

| Part # | Description | PSI | AMPS |
|----------------|-----------------|-----|------|
| ROLV5160PT03XB | 5 HP Stationary | 100 | - |

Professional Series

OMEGA
COMPRESSORS



- Contractor, Lt industrial use
- 2 year manufactures warranty on pump
- Low decibel level
- Durable cast iron pump
- Splash type lubrication
- Stainless steel valves
- Flywheel designed for excellent pump cooling
- Manual reset button for overload protection
- Built in regulator, pressure gauges and on/off switch
- Canadian company

| Omega Model | HP | Actual Fad - Cfm | Max Psi | Voltage | Tank Size | Pump Rpm | Amp Draw @ 125 Psi | Weight (lbs) |
|-------------|-----|---------------------------|---------|-----------|-----------|----------|--------------------|--------------|
| OMEPP6060V | 6 | 12.5@90Psi 11.0@125 Psi | 125 | 230V/1 Ph | 60 V | 1100 | 15 Amps | 300 Lbs |
| OMEPK6560V | 6.5 | 20.0@90Psi 18.0@125 Psi | 125 | 230V/1 Ph | 60 V | 1100 | 22 Amps | 330 Lbs |
| OMEPK5020VP | 5 | 7.8@90Psi 6.4@125 Psi | 125 | 115V/1 Ph | 20 V | 1100 | 15 Amps | 200 Lbs |
| OMEPK5020 | 5 | 7.8@90Psi 6.4@125 Psi | 125 | 115V/1 Ph | 20 V | 1100 | 15 Amps | 180 Lbs |

Portable Belt Driven Contractor Units

OMEGA
COMPRESSORS



- 2 Year manufactures warranty on pump
- Durable cast iron pumps
- Splash type lubrication
- Stainless steel valves
- Manual reset button for overload protection on belt driven units
- Dual control-stop/start with pressure switch or constant speed operation
- Low Rpm
- Flywheel designed for excellent pump cooling
- Built in regulator, pressure gauges and on/off switch.

| Omega Model | HP | Actual Fad - Cfm | Max Psi | Voltage | Tank Size | Pump Rpm | Amp Draw @ 125 Psi | Weight (lbs) |
|---------------|-----|-------------------------|---------|-----------|-----------|----------|--------------------|--------------|
| OMEPUK1508MDC | 1.5 | 6.6@90Psi 6.0@125 Psi | 125 | 115V/1 Ph | 8 | 1100 | 15 Amps | 214 Lbs |
| OMEPUK2008MDC | 2 | 9.5@90Psi 8.0@125 Psi | 125 | 115V/1 Ph | 8 | 900 | 22 Amps | 200 Lbs |

Omega Refrigerated Air Dryers

OMEGA
COMPRESSORS



- Removes moisture prolonging pneumatic tool life
- R134a Freon
- Compact design, easily serviced, wall mount slots
- Automatic electronic drains
- Illuminated on/off switch
- Hot gas solenoid valve
- High efficiency centrifugal moisture separator
- Canadian company

| Omega Model | Freon | Actual Fad - Cfm | Max Psi | Voltage | Pipe Size | Pump Rpm | Installation | Weight (lbs) |
|--------------|-------|------------------|---------|-----------|----------------|----------|---------------|--------------|
| OMEAMD Units | 134A | 3 - 20 Cfm | 175 | 115V/1 Ph | 3/8 - 3/4" Npt | 1100 | 20' From Unit | 62-75 Lbs |



2-Year Pump Warranty

Full warranty on any pump that fails within two years as long as basic regular maintenance is performed.

EZ Drain System

Easily use a single valve to drain both tanks as often as needed.

Durable

Roll cage protects the motor.

Easy to transport

Innovative vertical tank design improves balance and provides maximum maneuverability.

Driving Productivity

Electric Hand Carry Compressor (with Wheels)



- E-Z Drain – One ball valve drain located in control panel for simultaneous draining of both tanks
- Vertically Angled Tanks – Enables better center of gravity for easy transport throughout jobsite
- Roll Cage – For maximum durability and protection from jobsite conditions
- 2-Pole Induction Motor – Provides dBA of 80 to lessen the distraction while working in close proximity to compressor
- Recessed Control Panel – All gauges, regulator, couplers and drain valve are located in easy to reach position and are protected from jobsite conditions
- Contractor Grade Oil-lubed Pump – Extends product life for extra durability

| Part # | HP | CFM | RPM | Capacity | Weight |
|--------------|----|-----|------|-----------|-----------|
| BSTSTN150-18 | 2 | 4.2 | 3400 | 4 gallons | 72.7 lbs. |

Electric Wheelbarrow Compressor



- E-Z Drain - One ball valve drain located in control panel for simultaneous draining of both tanks
- Easy Load/Unload - Unique Handle Design allows for easy loading into back of truck and better balance when moving compressor throughout jobsite
- Cold Start Valve - Prevents compressor from blowing a fuse in cold weather conditions
- Cast Iron, Contractor Grade Oil-Lubed Pump - High durability and low maintenance
- Angled Control Panel - All gauges, regulator, couplers, safety valve and drain valve are located in easy to access location
- 2-Year Pump Warranty - Full warranty on any pump that fails within two years as long as basic regular maintenance is performed

| Part # | HP | CFM | RPM | Capacity | Weight |
|-------------|-----|-----|------|-----------|----------|
| BSTCET8-15W | 1.5 | 6.5 | 1725 | 8 gallons | 175 lbs. |

Gas Wheelbarrow Compressor



- E-Z Drain - One ball valve drain located in control panel for simultaneous draining of both tanks
- Easy Load/Unload - Unique Handle Design allows for easy loading into back of truck and better balance when moving compressor throughout jobsite
- Cold Start Valve - Provides easy start in cold weather conditions
- Cast Iron, Contractor Grade Oil-Lubed Pump - High durability and low maintenance
- Angled Control Panel - All gauges, regulator, couplers, safety valve and drain valve are located in easy to access location
- 2-Year Pump Warranty - Full warranty on any pump that fails within two years as long as basic regular maintenance is performed

| Part # | HP | CFM | RPM | Capacity | Weight |
|-------------|-----|------|------|-----------|----------|
| BSTCGT8-65W | 6.5 | 13.1 | 3200 | 8 gallons | 175 lbs. |